

#### Project:

Fixture Type: Location:

Contact:

Wall mounted • Wet location listed PROGRESS LED



# Description:

**WISH** 

LED wall lantern with etched white linen glass. Includes dark sky shield for full cut-off illumination or remove for a traditional lighting effect. 120V AC replaceable LED module, 1,211 lumens, 3000K color temperature and 90+ CRI.

## **Specifications:**

Black (-31) (powdercoat) Aluminum construction Etched White Linen glass cylindrical diffuser Dimmable (See Dimming Notes) Back plate covers a standard 4" hexagonal recessed outlet box Mounting strap for outlet box included 6" of wire supplied ENERGY STAR® qualified

## **Performance:**

nput Power   17w     nput Voltage   120 V     nput Frequency   60 Hz     Lumens/LPW   1211/71.2 (LM-79)     CCT   3000 K     CRI   90     Life (hours)   60,000 (L70/TM-21)     EMI/RFI   FCC Title 47, Part 15, Class B     Min. Start Temp   -30     Max. Operating Temp   5 year warranty		
nput Voltage   120 V     nput Frequency   60 Hz     numens/LPW   1211/71.2 (LM-79)     CCT   3000 K     CRI   90     Life (hours)   60,000 (L70/TM-21)     EMI/RFI   FCC Title 47, Part 15, Class B     Vin. Start Temp   -30     Max. Operating Temp   5 year warranty	Number of Modules	1
nput Frequency 60 Hz   numens/LPW 1211/71.2 (LM-79)   CCT 3000 K   CRI 90   Life (hours) 60,000 (L70/TM-21)   EMI/RFI FCC Title 47, Part 15, Class B   Min. Start Temp -30   Max. Operating Temp 30 °C   Warranty 5 year warranty	Input Power	17w
Lumens/LPW 1211/71.2 (LM-79)   CCT 3000 K   CRI 90   Life (hours) 60,000 (L70/TM-21)   EMI/RFI FCC Title 47, Part 15, Class B   Vin. Start Temp -30   Max. Operating Temp 30 °C   Warranty 5 year warranty	Input Voltage	120 V
CCT   3000 K     CRI   90     Life (hours)   60,000 (L70/TM-21)     EMI/RFI   FCC Title 47, Part 15, Class B     Vin. Start Temp   -30     Max. Operating Temp   30 °C     Warranty   5 year warranty	Input Frequency	60 Hz
CRI90Life (hours)60,000 (L70/TM-21)EMI/RFIFCC Title 47, Part 15, Class BVin. Start Temp-30Max. Operating Temp30 °CWarranty5 year warranty	Lumens/LPW	1211/71.2 (LM-79)
Life (hours)60,000 (L70/TM-21)EMI/RFIFCC Title 47, Part 15, Class BMin. Start Temp-30Max. Operating Temp30 °CWarranty5 year warranty	ССТ	3000 K
EMI/RFIFCC Title 47, Part 15, Class BVin. Start Temp-30Max. Operating Temp30 °CWarranty5 year warranty	CRI	90
Min. Start Temp-30Max. Operating Temp30 °CWarranty5 year warranty	Life (hours)	60,000 (L70/TM-21)
Max. Operating Temp30 °CWarranty5 year warranty	EMI/RFI	FCC Title 47, Part 15, Class B
Warranty 5 year warranty	Min. Start Temp	-30
	Max. Operating Temp	30 °C
	Warranty	5 year warranty
Labels cCSAus Wet location listed	Labels	cCSAus Wet location listed
ENERGY STAR <sup>®</sup> qualified		ENERGY STAR <sup>®</sup> qualified

# P6085-3130K9

#### Images:



## **Dimensions:**

Width: 9" Height: 12-1/2" Depth: 10-1/2" H/CTR: 3-1/8" (facing up)

Glass Width: 5-5/16" Height: 7-3/8"



# WISH

Wall mounted • Wet location listed PROGRESS LED



nergy

# **Dimming Notes:**

P6085-3130K9 is designed to be compatible with many Electronic Low Voltage (ELV/Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls.

# **Dimming Controls**

Lutron Diva DVELV-300P	
Lutron Nova T NTELV-300	
Lutron Diva DVELV-300P	
Luton Caseta	
Lutron Ariadni AY-600P	
Leviton Illumatech IPI06-1LZ	
Lutron Lumea LG-603PG	
Leviton SureSlide 6672	
Leviton SureSlide 6674	
Lutron Ariadni AYCL-153P	
Lutron Skylark Contour CTCL-153P	
Lutron Diva DVCL-153P	
Pass & Seymour Harmony DCL453PTCCCV6	
Lutron Toggler TGCL-153P	
Lutron Maestro MACL-153M	
Lutron Ariadni AYLV-600P	
Lutron Maestro MA-600	
Lutron NOVA T NTLV-600	
lutron Maestro MAELV-600	
Lutron spacer/system SPSELV-600	
Lutron Renoir II AWRMG-EAW	

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.