

# P6346 Flood Light With Spike

In ground mounted • Wet location listed



## Description:

The LED swivel stake mount Security flood light has tempered glass and rugged die-cast construction. This light can be used on pathways, for accent lighting and security. 1,115 lumens 3000K color temperature, 83 CRI. 6-3/4" stake with 8" cord. Adjustable swivel for easy adjustment. IP65 rated.

## Specifications:

- Bright White (-28) (Powder Coat Paint)
- Die-cast aluminum construction
- Tempered glass lens
- Spike for ground installation.
- 1115 lumens, 84.5 lumens/watt
- Use on landscaping, pathway, accent, security, safety and general lighting.
- 6" of wire supplied
- 

## Performance:

Number of Modules	1
Input Power	13w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1115/84.5 (LM-79)
CCT	3000 K
CRI	83
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	40 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed

## P6346-2830K

## Images:



## Dimensions:

- (A) Diameter: 3-3/4"  
 (C) Depth: 3-1/4"  
 (B) Height: 13-1/2"

