

Arlo LED Vanity ARLV Series

Features

LED contemporary style. Satin nickel finish with frosted acrylic diffusers provide a modern geometric design to this wall vanity. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All exposed metal is finished in satin nickel.

Diffuser

Diffusers are made from a thick frosted acrylic.

Electrical

Input 120V / 60Hz for D1 model and 120-277VAC / 60Hz for MV model. Compatible with residential (TRIAC/ELV) dimming only at 120 VAC (D1).

LED

Integrated LED modules capable of producing: 25" - 30W, 1800 source lumens 33" - 40W, 2400 source lumens 3500K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for damp locations. ENERGY STAR® qualified (MV only). ADA

Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

		Source				
Satin Nickel	LED	Lumens	CCT	L	Н	D
ARLV250418L35D1SN (3-Light)	30W	1800	3500K	25"	4"	3-3/4"
ARLV250418L35MVSN (3-Light)*	30W	1800	3500K	25"	4"	3-3/4"
ARLV330424L35D1SN (4-Light)	40W	2400	3500K	33"	4"	3-3/4"
ARLV330424L35MVSN (4-Light)*	40W	2400	3500K	33"	4"	3-3/4"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	







