

LED M6 2030 / LED M6 2436 **BATHROOM MIRROR** w/ LED Lighting and Defogger INSTALLATION GUIDE



IMPORTANT SAFETY INSTRUCTIONS

When using an electrical furnishing, basic precautions should always be followed, including the following:



DANGER

READ AND FOLLOW ALL INSTRUCTIONS BEFORE USING THIS MIRROR.

WARNING To reduce the risk of burns, fire, electric shock or injury to persons. Use this furnishing only for its intended use as described in these instructions. Do not use attachments not recommended by the manufacturer. Never drop or insert any object into any opening. Do not use outdoors.

> WARNING Risk of electric shock. Connect this furnishing to a properly grounded circuit only. See Grounding instructions.

GROUNDING INSTRUCTIONS:

This product must be connected to a grounded metal, permanent wiring system, or an equipment-grounding conductor must be run with the circuit conductors and connected to the equipment-grounding terminal or lead on the product.

WARNING An Electrical option cabinet must be wired to a 20 Amp GFI (Ground Fault Interrupter) protected circuit when used in bathrooms and all other locations required by the National Electric Code.

PLEASE SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE

LED M6 2030 / LED M6 2436

INSTALLATION GUIDE

PAGE 1





LED M6 2030 / LED M6 2436 **BATHROOM MIRROR** w/ LED Lighting and Defogger **INSTALLATION GUIDE**



ELECTRIC CONNECTIONS

ALL WIRING SHOULD BE DONE BY A QUALIFIED LICENCED ELECTRICIAN

WARNING: Shut off power before wiring the mirror.



WARNING: An Electrical option mirror must be wired to a 20 Amp GFI (Ground Fault Interrupter) protected circuit when used in bathrooms and all other locations required by the National Electric Code.

WARNING: This mirror must be connected to a grounded, metal permanent wiring system or an equipment-grounding conductor must be run with the circuit conductors and connected to the equipment grounding terminal or lead on the mirror.

Make connections | Live to black

CAUTION: Requires 120 VAC 20 Amp GFI protected circuit.



Ground to green. Live / Black **Field Wire** Ground / Green Neutral / White *Wire terminal plate is not included. **MIRROR FEATURES** • 5mm copper free silver mirror High output LED lighting: CRI 90+, 2700-6400K CCT, IP44 Color Temperature changing and dimmable touch switch for surface LED Electric wiring: Be sure to provide enough Vertical and horizontal mount options wire to make the proper and safe Defogger connection to the Field/Power.

Neutral to white

LED M6 2030 / LED M6 2436

INSTALLATION GUIDE



FINAL ASSEMBLY

How to use Defogger Switch and Dimmer Switch:

Touch (b) to turn the task light and defogger on or off.

Press and hold (to change the color temperature of task light.

Press and hold (to dim or brighten the task light.

Use and Maintenance:

CAUTION:

Mirror and mirror's body are constructed of mirrored glass and aluminum. Use a damp cloth to clean your mirrors. Do not use any abrasive material as it may damage the surface and finish of the mirror. A mild detergent may be used to clean the surfaces of the mirror. When cleaning spray the cloth, not the mirrors or surrounding surfaces.

TROUBLESHOOTING:

For service and parts information please email:

Info@BlossomUS.com

Please visit our website for more information.

www.BlossomUS.com