

# User's Manual






# BEFORE INSTALLATION


This product has been inspected and debugged by the factory to the best condition. Please do not disassemble and assemble it yourself.




Before installing the faucet, please be sure to remove sundries and sludge from the water pipe to prevent sundries from blocking the faucet.




1. Please read the manual firstly before installation;
2. Please check the condition of all the parts, and the installation tools are not included, please prepare it by yourself;
3. User manual includes matters needing attention during installation, please keep it properly;
4. The size chart in the manual is for reference only, please refer to the actual product that you receive.




Embedded depth:  
**2.6\"~2.8\"**




## Recommend Tools :




PTFE Tape



Hex Key



Slotted Screwdriver





Phillips Screwdriver

1. The sundries at the connection area must be cleared before installation to avoid blockage or leakage;
2. Connect the inlet pipe correctly as shown in the figure;
3. The maximum temperature of hot water is not higher than 80°C (176°F);
4. Please contact seller for consultation if you need to install in other method.


# INSTALLATION STEPS

1. First bury the main part in the wall.




2. Please install other parts in the order as shown in the figure below when the valve mounted to the wall:


- 1.Remove the lid of the Embedded Box;
- 2.Place the trim plate;
- 3.Mount the handles.




3. Install the shower arm and shower head.  
(Wrap the PTFE tape on the thread.)



4. Install the hand shower seat.



# INSTALLATION DIMENSION



The picture is for reference only, you can install it according to your own requirements.

## CLEANING CARE

In order to keep the appearance of faucet clean, bright and good performance, please take care of the faucet as follows;

1. Rinse with water only and dry with soft cotton cloth;
2. Use mild liquid and colorless glass cleaner to remove surface dirt and scale film, or use polish without abrasive effect;
3. Do not use abrasive detergent, polish, emery cloth, paper towel or scraper, etc.;
4. Do not use acid cleaner, or cleaner and soap with insoluble gran etc.;
5. In the process of use, mud may accumulate in the bubbler and make the water flow slow, The bubbler can be unscrewed, rinsed with water, and then installed back in place.



