

INSTALLATION INSTRUCTIONS

LED WALL SCONCE

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Min 90°C supply conductors. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

1. Shut off the power at the circuit breaker and remove existing fixture, including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Be careful not to lose any small parts necessary for installation.
3. Thread out the four mounting screw from the back plate, and then take out the mounting plate.
4. Align the mounting slots of the wall plate with holes of the outlet box. Mark the location of the keyhole slots on the wall. Drill a 1 holes at the narrow end of each keyhole slot marking on the wall. Carefully hammer a wall anchor into each drilled hole.
5. Replace the mounting wall plate over junction box. align the narrow end of each keyhole slot with its respective wall anchor. Feed the anchor screws through keyhole slots and thread them into the wall anchors until wall plate has been flushed against the wall. Fasten the wall plate to thread holes in outlet box using two outlet box screws.
6. Connect black fixture wire to the black supply wire with a suitable wire connector. Connect white fixture wire to the white supply wire with a suitable connector. After wires are connected, tuck them carefully inside the switch box.
7. Place the fixture base over the mounting wall plate and secure it to the wall plate by using four mounting screw.
8. The two thumb screw are fixed to the fixture through the two mounting holes and tubes of the Diffuser.

DIMMING

This fixture features electronic Traic dimming capabilities. To utilize TRAIC dimming: use wires black (hot), white (neutral) and bare copper ground wire (ground).

