


Project:

REALS Up/Down LED Sconce Spec Sheet

SKU: 7302.FW.PL.72-WL Learn more at:
<https://sonnemanlight.com/real-up-2fdown-led-sconce>

Description: Consider the possibilities of the nearly unlimited opportunities to configure REALS sconces, with lenses and caps, for a variety of LED illuminating possibilities. Also available as a [Downlight Sconce](#), [Surface Mount](#), [Bollard](#), and [Double Bollard](#).

Type #:



Dimensions

| | |
|-------------------------------|------|
| Height: | 2.5" |
| Width: | 5" |
| Extends: | 6.5" |
| Minimum Extension: | 6.5" |
| Maximum Extension: | 6.5" |
| Canopy/Backplate/Base Width: | 4.5 |
| Canopy/Backplate/Base Depth: | 0.5 |
| Canopy/Backplate/Base Height: | 4.5 |

Electrical Specs

| | |
|------------------------|--------------|
| Bulb(s) Included?: | Yes |
| Bulb 1 Type: | Integral LED |
| Bulb Quantity: | 2 |
| Input Voltage: | 120VAC |
| Wattage: | 20 |
| Initial Lumens: | 2080 |
| Color Temperature: | 3000K |
| CRI: | 90 |
| Power Supply Type: | Driver |
| Power Supply Quantity: | 1 |
| Power Supply Location: | Outlet Box |
| Dimming Type: | TRIAC/ELV |
| Bulb Max Wattage: | 20 |

Installation

| | |
|---------------------------|-------------------------------|
| Installation: | Licensed electrician required |
| Installation Orientation: | Vertical |

Shipping

| | |
|------------------------|---------------|
| Carton 1 L x W x H: | 9" X 10" X 9" |
| Carton 1 Gross Weight: | 4 LBS |
| Fixture Weight: | 3 |

Shade

| | |
|-------------------|---|
| Lens Type: | White Cylinder Lens and Plate Lens |
| Shade 1 Material: | Aluminum w/White Polycarbonate |
| Shade 2 Material: | Frosted White Polycarbonate |

Available Finishes

Available Finishes: Textured Bronze (.72),
Textured Gray (.74), Textured White (.98)

General Listings

| | |
|--------------------|--------------------------|
| Features: | Wet Rated |
| Certification: | C-ETL-US |
| Color/Finish: | Textured Bronze (.72) |
| Dark Sky Friendly: | Y |