

the CELESTA SERIES

Classic. Traditional. Streamlined.

STANDARD SIZED - VALUE PRICED

Adjustable Door & Panel CELA-935

Introducing the new Celesta Adjustable Width enclosure, now available in our RODA by Basco line.

This unit provides a luxury door perfect for most applications that require minimal out of square or out of plumb alignment.

The CELA-935 is designed to fit the most popular opening sizes with its innovative U-Channel system.



*Celesta Door & Panel with Adjustable Width (CELA-935)
featuring 3/8" Clear Glass with Brushed Nickel Finish*

RODA BY BASCO

BECAUSE THE SHOWER IS EVERYTHING

Features

- Celesta Euro-style Door & Inline Panel
- 8" Euro-style through-the-glass pull handle
- Celesta wall mount hinges, swing both in and out
- 3/8" (10 mm) thick tempered glass available in two options
- 1" adjustment range provides increased plumb and level tolerance
- Anodized aluminum hardware prevents rusting or corrosion
- Reversible for left or right installation
- U-Channel width = 1 1/2"

3/8" Glass Options

- Clear (CL)
- AquaGlideXP Clear (XP)

Frame Options

- Chrome (SV)
- Brushed Nickel (BN)
- Oil Rubbed Bronze (OR)



| Model | Unit Width (Opening Size*) | Panel Width | Unit Height |
|------------------|----------------------------|-------------|-------------|
| • CELA-935-46-72 | 45" - 46" | 16 3/8" | 72" |
| • CELA-935-47-72 | 46 1/16" - 47" | 17 3/8" | 72" |
| • CELA-935-58-72 | 57" - 58" | 28 3/8" | 72" |
| • CELA-935-59-72 | 58 1/16" - 59" | 29 3/8" | 72" |
| • CELA-935-46-76 | 45" - 46" | 16 3/8" | 76" |
| • CELA-935-47-76 | 46 1/16" - 47" | 17 3/8" | 76" |
| • CELA-935-58-76 | 57" - 58" | 28 3/8" | 76" |
| • CELA-935-59-76 | 58 1/16" - 59" | 29 3/8" | 76" |

*Measurements after walls are finished.

Installation Notes

- Install this product according to the installation guide.
- Not recommended for fiberglass.
- Minimum of 2" threshold required.
- The base and walls for any RODA unit must be constructed with proper wood blocking prior to installation to ensure the weight of the enclosure is properly supported as it may result in product failure. At minimum, 2 x 4 blocking is required at the location of any structural member of the unit. All fasteners at these locations are required to be installed into the blocking.

Applicable Codes/Standards

Specified model meets or exceeds the following:

- ASTM C1464-06 and ASTM C1048
- Safety criteria CPSC16 CFR 1201 categories 1 & 2 and ANSI Z97.1
- SGCC Certification required.

16 CFR 1201 II
ANSI Z97.1-20XX
10mm UA SGCC XXXX

