


# BLITZEN

## F-060

54" Ceiling Fan

# WAC SMART FANS



### PRODUCT DESCRIPTION

A sleek design incorporated with advanced technology and flexible control solutions defined. Blitzen is available in three finishes—Matte Black, Matte White and Brushed Nickel. A deluxe smart ceiling fan for fine interiors and exteriors.

### FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Luminaire not included
- Includes remote control with wall cradle (RC20-WT)
- Wall control for 3, 4-way control sold separately
- Compatible with WAC app \$9.95 per fan + applicable tax

### AIRFLOW/ENERGY EFFICIENCY

<b>Weighted-Average/High Airflow CFM:</b>	4102/6034
<b>Weighted-Average/High Energy Use (W):</b>	18/31.5
<b>Estimated Yearly Energy Cost (\$):</b>	\$5.62
<b>High Efficiency (CFM/W):</b>	192
<b>Max RPM:</b>	167

### ORDER NUMBER

Model	Housing	Blade
<b>F-060</b>	<b>BN</b> <i>Brushed Nickel</i>	<b>TT</b> <i>Titanium Silver</i>
	<b>MB</b> <i>Matte Black</i>	<b>MB</b> <i>Matte Black</i>
	<b>MW</b> <i>Matte White</i>	<b>MW</b> <i>Matte White</i>

### F-060-\_\_

Example: **F-060-MB**

**\*This fan comes uni-pack - blade select options are not available**

**\* Range results may vary based on application and surroundings.**

### SPECIFICATIONS

<b>Construction:</b>	Steel, Plywood
<b>Blade:</b>	14° Pitch, 54" sweep
<b>Downrod:</b>	3/4"W X 6"H included
<b>Mounting Slope:</b>	Up to 32°
<b>Wire:</b>	80"
<b>Hanging Weight:</b>	16.5 lbs
<b>Total Power:</b>	31.5W
<b>Standards:</b>	UL/cUL Damp Location listed, Title 24 JA8-2016 Compliant, Title 20 Compliant, Energy Star Rated
<b>Motor Type:</b>	120 x 20 sensorless DC motor

### WIRELESS PERFORMANCE

<b>Wi-Fi Range:</b>	Up to 150 ft*
<b>Bluetooth Range:</b>	Up to 150 ft*

The WAC app synchronizes seamlessly with smart home devices you already own



waclighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

### OPTIONAL ACCESSORIES

<p>Bluetooth Wall Control</p>		<p><b>WC20-</b></p>	<p><b>WT</b> White</p>	<p>Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.</p>
<p>Bluetooth Remote Control</p>		<p><b>RC20-</b></p>	<p><b>WT</b> White</p>	<p>Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with WAC Smart Fans. Includes easy-to-install wall cradle and batteries.</p>
<p>Downrod</p>		<p><b>DR12-</b> 12IN  <b>DR18-</b> 18IN  <b>DR24-</b> 24IN  <b>DR36-</b> 36IN  <b>DR48-</b> 48IN  <b>DR60-</b> 60IN  <b>DR72-</b> 72IN</p>		<p>All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.</p>
<p>Downrod Couplers</p>		<p><b>DC-</b></p>	<p><b>BN</b> Brushed Nickel  <b>MB</b> Matte Black  <b>MW</b> Matte White</p>	<p>Connects two downrods together.</p>
<p>Sloped Ceiling Kit</p>		<p><b>SC-</b></p>		<p>Designed to accommodate buildings with steeper sloped ceilings up to 45o or 12/12 pitch.</p>

Examples: Wall Control - **WC20-WT**, Remote Control - **RC20-WT**, Downrod - **DR12-BN**, Downrod Coupler - **DC-MB**, Sloped Ceiling Kit - **SC-MW**

### SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

### SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13o	14-17o	18-21o	22-25o	26-29o	30-32o	33-35o	36-38o	39-41o	42-44o	45o
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

**NOTE:** Recommended maximum downrod length of 72" with 80" lead wire