KOHLER_®

Features

- Vitreous china.
- Elongated bowl.
- AquaPiston[®] flushing system.
- One-piece.
- Includes seat and cover.
- Includes trip lever.
- 1.28 gpf (4.8 lpf).
- 12" (305 mm) rough-in.
- 2-1/8" (54 mm) glazed trapway.
- 11" (279 mm) x 8-3/4" (222 mm) water area.
- 28-1/8" (714 mm) x 18-1/4" (464 mm) x 28-1/2" (724 mm).

Recommended Accessories

K-75796 Cachet® Nightlight Quiet-Close™ Elongated Toilet Seat K-4108 C3®-230 Elongated Cleansing Toilet Seat K-5420 Low-Profile Bolt Caps K-9167-L Trip Lever K-484 Trip Lever 1023457 Wax Ring/Hardware Kit 1265114 Connector Hose

Components

Product includes:

K-4733 Glenbury[™] Quiet-Close[™] Elongated Toilet Seat Additional included component/s: Tank cover, Trip lever, Bolt cap accessory pack, and Tank accessory pack.





Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense® ADA ICC/ANSI A117.1 CSA B651 OBC

KOHLER[®] One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color Code Description

	-
0	White
96	Biscuit
47	Almond
NY	Dune
95	lce™ Grey
G9	Sandbar
33	Mexican Sand™
K4	Cashmere
58	Thunder™ Grey
-	



Memoirs[®] Stately Comfort Height[®] Toilet

K-3813



Memoirs® Stately

Comfort Height[®] Toilet K-3813



Technical Information

All product dimensions are nominal.			
Toilet type:	One-piece, Floor-mount		
Waste Outlet:	Floor		
Bowl shape:	Elongated front		
Flush type:	AquaPiston [®]		
Seat hinge type:	Quiet-Close™, Quick-Release™		
Trap passageway:	2-1/8" (54 mm)		
Water Consumption Full:	1.28 gpf (4.8 lpf)		
Water surface size:	11" x 8-3/4" (279 mm x 222 mm)		
Rim to water surface:	6" (152 mm)		
Rough-in:	12		
Seat-mounting holes:	5-1/2" (140 mm)		

Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.

