


SAFAVIEH LIGHTING

Assembly Instruction

CAUTION: Read instruction carefully and turn electricity off at main circuit breaker panel before beginning installation.

ITEM#:LIT4520A



Care and Cleaning

To clean the outside of the fixture, use a dry or slightly dampened clean cloth(use clean water, never a solvent)to wipe the surface of the fixture.

To clear the inside of the fixture, first disconnect power to the fixture by turning off the circuit breaker or by removing the fuse at the fuse box. Next, use a dry or slightly dampened clean cloth(use clean water, never a solvent) to wipe the interior surface of the fixture

Do not use any cleaners with chemical, solvents or harsh abrasives. Use Only a dry soft cloth to dust or wipe carefully.

Estimated Assembly Time:30 minutes


Part List and Hardware List

PIECE	DESCRIPTION	PICTURE	QUANTITY	PIECE	DESCRIPTION	PICTURE	QUANTITY
A	Wire Nut		3X	G	Lamp Boby		1X
B	Mounting Plate		1X	H	Closable link/cap		2X
C	Bulb		1X	I	Hanging Loop		2X
D	Mounting Screw		2X	J	Chain		1X
E	Canopy		1X	K	Socket		1X
F	Ball Nut		2X				

Installation


Step 1

Unpack all parts from cartons carefully.
Separate the Mounting Plate(B) from the Canopy(E) by removing the Ball Nuts(F) anti-clockwise.




Step 2

Screw the Chain(J) to the Hanging Loop(I) of the Canopy(E) and of the fixture body with Closable link/cap (H) as diagram.




Step 3

Weave the 2 wire power cord and bare ground wire through every other loop to the top of chain(J),center holes of Hanging Loop(I)&Canopy(E)&Mounting Plate(B) as diagram.



Step 4 Wire connection

Connect,Hot,Black or Red outlet Supply Wire to:	Connect,Neutral,White Outlet Supply Wire to:
Black	White
*Parallel Cord(round&smooth)	*Parallel Cord(square&ridged)
Clear,Brown,Gold or Black without Tracer(colored stripes)	Clear,Brown,Gold or Black without Tracer(colored stripes)
Insulated Wire(not green)with copper metal conductor	Insulated Wire(not green)with Silver metal conductor



*Note: When parallel wire(SPTI&SPTII)is used. The neutral wire is square shaped and ridged and the hot wire will be round in shape and smooth.(See illustration on left)



Grounding Instructions:

- a) For installation in the United States: Wrap ground wire from outlet box around green ground screw on mounting bracket, no less than 2" from wire end. Tighten ground screw. If fixture is supplied with a ground wire, connect to outlet ground wire with a wire connector.
- b) For installation in Canada: If fixture is supplied with ground wire, wrap ground wire around green grounding screw on mounting bracket. Tighten ground screw.

Step 5

Attach the Mounting Plate (B) onto the junction box by inserting two Mounting Screws (D) and turning clockwise till tight.

Position the Canopy (E) over the Mounting Plate(B),fix the Canopy(E) by rotating the Ball Nut(F)clockwise until secure. Do not over tighten.

Insert the bulb(C) into the socket(K) until secure.
DO NOT EXCEED THE SPECIFIED WATTAGE.

**PLEASE USE TYPE "A" BULB MAX 100-WATT
OR CFL BULB MAX 23-WATT OR LED MAX 12-WATT
THERE IS 1*9W LED BULB IN THE BOX.**

Step 5

Consult a qualified electrician to ensure correct branch circuit conductor

ENJOY YOUR LAMP

