

Assembly Instruction Sheet #S-1375W24
For Style 1375W24

Tools Required: Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.

Light Sources: (1) 120V LED 3W DIMMABLE (3000K)

Estimated Assembly Time: 15-30 minutes

Preparation: Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the boiler. Contact customer service for replacement parts.

Warnings and Cautions

Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt.

These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation.

Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.


Package Contents



A Fixture Body x1

Hardware Contents

PART	DESCRIPTION	QUANTITY
BB	Wire nut	2pcs
CC	Screw	2pcs



STEP 1-Release Mounting bracket from Ceiling Canopy.





Figure 1

STEP 2 – Attach Mounting bracket to Outlet Box


Attach the Mounting bracket (EE) to the Outlet Box with the head of the Green Ground Screw facing you.

Secure it with Outlet Box Screws.


Tighten until snug.

**Figure 2**



STEP 4 - Install Ceiling Canopy to Ceiling

**Figure 4**

STEP 3 - Wire Connections



STEP 5 – Install tube.

**Figure 3****Figure 5**