

# HELM

Wall or ceiling mounted • Damp location listed



## Description:

Helm is a uniquely styled series with design flexibility. This contemporary square fixture has an acrylic diffuser with architectural detail. Can mount to ceiling or wall. Two-light LED fixture. 3000K, 90+CRI 1,211 lumens per module.

## Specifications:

- Antique Bronze (-20) (painted)
- Steel construction
- White acrylic diffuser
- 120VA replaceable LED Module (part # 93053641)
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" - ADA
- ENERGY STAR® qualified

## Performance:

Number of Modules	2
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1211/71.2 (LM-79) per module
CCT	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified

## P3448-2030K9

## Images:



## Dimensions:

Square: 14"  
Height: 3-3/4"  
Depth: 3-3/4"  
H/CTR: 7"

Glass  
Width: 11-13/16"  
Height: 3-5/8"

**P3448-2030K9****Dimming Notes:**

---

P3448-2030K9 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron Nova T NTELV-300

Lutron Verti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.  
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.