




Calx 19, walnut, brushed brass

**Calx 19**  
pendant



Dimensions: 13" x 13", 12.75"  
Materials: wood, metal, polymer  
Product weight: 7 lb  
Suitable for a sloped ceiling

**Integrated LED Specifications**  
Light output: 1250 Lumens (source)  
Light color: 2700 K or 3500 K  
Color accuracy: 90+ CRI  
Power usage: 13 W  
Dimmable (see driver below)  
White (CM-060) extended-profile round canopy with white braided cord and steel cable included  
Canopy dimensions: 5"Ø, 2"  
Canopy required to house LED driver (3.3" x 1.6" x 1.0")  
See below for more canopy information  
72" drop length, field adjustable

**Medium Base Specifications**  
Lamping: 1x E26 base, type A lamp, 60 W max  
Bulb not included  
Input voltage: 250 V AC max  
White (CM-060) low-profile round canopy with white SPT cord and steel cable included  
Canopy dimensions: 5"Ø, 0.3"  
72" drop length, field adjustable  
Suitable for a sloped ceiling  
Wood grain will vary  
Specifications subject to change



brushed brass  
(CM-047)



brushed aluminum  
(CM-012)




brushed rose gold  
(CM-046)



walnut  
(CM-055)



dark stained walnut  
(CM-056)



Calx 19 E26  
low-profile round  
canopy with white SPT  
cord with steel cable



Calx 19 Integrated LED  
extended-profile round  
canopy braided cord  
with steel cable



The Calx is an example of modern design where the methods and the materials themselves are integral to its very conception, aligning form and function, which creates a synergy that is evident. The fixture ultimately forms a square aperture but enjoys a beautifully simple faceted structure.

Nick Sheridan,  
Designer

**MATERIAL & FINISH OPTIONS**

Calx 19 part # 06-200-19

**Metal Finish**

- brushed aluminum (CM-012) A
- brushed rose gold (CM-046) G
- brushed brass (CM-047) R

**Wood Finish**

- walnut (CM-055) W
- dark stained walnut (CM-056) D

**Lamping**

- 2700 K LED 27
- 3500 K LED 35
- medium base E26 socket MB

**Driver (LED version only)**

- 120-277 V AC input voltage
- 0-10 V dimming
- TRIAC and ELV dimming at 120 V AC only P1

**Includes**

- frosted polymer diffuser (CM-057)

