

## **LED Copper Hat**



PROJECT:

TYPE: ORDERING # :

COMMENTS:

## FEATURES

- Design Pro LED in a definitive yet unassuming copper housing. Will develop a natural verdigris over time.
- Unfinished Copper Housing (copper will naturally patina over time).
- 4 W / 5.8 VA, Integrated LEDs and Driver, 2950K (-150/+175), High CRI.
- 9V 15V AC/DC
  - 30" of usable #18-2, SPT-1-W leads. Cable connector supplied.
- 8" In-ground stake



ORDERING INFORMATION							
EXAMPLE: 15850CO (Product # & Finish)							
PRODUCT	FINISH	WATTAGE	LIGHT SOURCE	WIRING	MOUNTING ACCESSORIES (INCLUDED)	OPTIONS & ACCESSORIES	
<b>15850</b> Dimensions: 6" W x 21.5" L	Cast Aluminum CO - Unfinished Copper	4 W / 5.8 VA Note: Not for use with electronic transformers.	Integrated LEDs and Driver 2950K (-150 / +175) High CRI	30" of usable #18-2, SPT- 1-W leads. Cable connector supplied.	8" In-ground stake	<ul> <li>15601AZT - Cast Aluminum Surface Mounting Flange w/ Bronze Finish, Neoprene Gasket For Watertight Seal</li> <li>15601BKT - Cast Aluminum Surface Mounting Flange w/ Black Finish, Neoprene Gasket For Watertight Seal</li> <li>15601BBR - Cast Brass Surface Mounting Flange, Neoprene Gasket For Watertight Seal</li> <li>Flange For Tree / Surface Mounting 15607AZT - Textured Bronze Finish</li> <li>15607BKT - Textured Black Finish</li> <li>15607BBR - Bronzed Brass Finish</li> </ul>	
	Fixture Photometric (fc)						
Distance from Light         0'         1'         2'         3'         4'         5'         6'         7'         8'           Footcandles         8.77         6.57         4.37         2.77         1.77         1.57         0.61         0.41         0.28							



For Warranty Information, please visit www.landscapelighting.com

## NOTES

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.