Submitted Model No.: Specific Features:



▲ Designate proper finish suffix

Spray Patterns



Your Delta Faucet handshower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Delta can do

ACTIVTOUCH® HANDSHOWER

Three Spray Selection Buttons "Pause Control" Button

STANDARD SPECIFICATIONS:

- Maximum 2.5 gpm @ 80 psi, 9.5 L/min @ 550 kPa (51504, 54424-PK, 55424, 59424-PK)
- Maximum 1.75 qpm @ 80 psi, 6.6 L/min @ 550 kPa (54424-18-PK, 59424-18-PK)
- Nine spray settings pause is a non-positive shut-off Three spray selection buttons for a simple
- one-handed push of a button
- 60"-82" stretchable metal hose: 51504, 55424, 54424
- 28" contemporary adjustable wall bar: 51504
- Adjustable wall mount: 55424
- Adjustable shower arm mount: 54424
- ADA compliant grab bar when installed per accessibility guidelines of the act

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1 ◆
- EPA WaterSense[®]
- Indicates compliance to ICC / ANSI A117.1

Delta Faucet Company

55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2017 Delta Faucet Company