WEAVE I FANDELIER 60010BZGTGLD

- FTL/cFTL
- Title 20 listed
- LED 3000K
- Suitable for Dry location
- Wall mountable (remote control included)

Job Name	:
Job Type	:
Quantity	:
Comments	



ACCESSORIES (Sold Separately)



FCT6000WT Fandelier Wall Control


PRODUCT DESCRIPTION

Maxim Lighting is proud to add the Weave fandelier to one of our most-sought after signature lighting collections. The Weave fandelier features a stunning ring of metal bands woven together and finished with hand painted Bronzed Gilt on the outside and contrasting Gold Leaf on the inside. LED lighting illuminates the space with a warm and inviting glow while the seamlessly integrated fan circulates the air for optimal comfort.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:

D

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs



D

MEASUREMENTS DIMENSIONS

CANOPY HANGING WEIGHT : 28.09 lb BLADE **BLADE PITCH** BLADE TO CEILING : 13.75"H

LAMPING

INPUT VOLTAGE LUMENS BULBS DIMMABLE CRI COLOR TEMP MOTOR TYPE

AIRFLOW

SPEEDS :6 AIRFLOW CFM : 5057 ELECTRICITY USE · 31 90W AIRFLOW EFFICIENCY: 158.5

: 33"D x 18.5"H : 7"D x 2.75"H : 3 Blades with 22" span : Varying

: 4158 Rated (2000 Del.)

: 46W PCB LED (Bulb included)

:120V

: Yes

: 80+

: 3000K

: DC Motor

FINISHES OPTIONS:

Bronze Gilt / Gold (BZGTGLD)

MATERIAL:

Steel Aluminium Polypropelene Fan Blades

INCLUDES

Wall Mountable Remote Control

• 1 x 8" Downrod

DOWNROD OPTIONS

- 18" (FRD0118BZGT)
- 24" (FRD0124BZGT)
- 30" (FRD0130BZGT)
- 36" (FRD0136BZGT)

RATINGS:

ETL CETL Dry Location Title 20



ADDITIONAL: RATED LIFE: 35,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) LIGHTING DIRECTION: Out

G н

WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com