

Levity® Frameless Sliding Bath Door K-706000-L

Features

- Innovative roller design simplifies installation and provides out-of-plumb adjustability while glass is installed.
- Cushioned center guide provides smooth, quiet sliding action.
- Vertical blade handles accentuate the contemporary style.
- CleanCoat®+ glass coating creates a hydrophobic barrier that repels water, soap scum, and residue, saving time and protecting shower doors 10 times longer than original CleanCoat. (Based on 2021 internal wear/abrasion testing using a microfiber cloth.)

Material

Frameless, 1/4" (6 mm) thick Crystal Clear tempered glass.

Installation

- Sliding bath door.
- Not for use in hospitality.

Included Components

Additional Components: Hardware kit



Codes/Standards

CPSC 16CFR 1201 ANSI Z97.1

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	SH	Bright Silver
	MX	Matte Nickel
	ABV	Anodized Brushed Bronze
	2MB	
	ABZ	Anodized Dark Bronze
	BL	Matte Black


Available Glass Options Code Description

L Crystal Clear





Levity® Frameless Sliding Bath Door K-706000-L



Technical Information

All product dimensions are nominal.

Installation type: For bath installation Opening style: Sliding/Bypass Opening Width - 56-5/8" (1438 mm)

Min:

Opening Width - 59-5/8" (1514 mm)

Max:

Walk-through - Min: 24-3/8" (619 mm)
Walk-through - Max: 27-3/8" (695 mm)
Base-To-Wall 1/2" (13 mm)

Radius - Max:

Glass thickness: 1/4" (6 mm)
Glass coating: CleanCoat®

Notes

Install this product according to the installation guide.

If replacing a shower door, the narrow wall jamb design of this door may not cover the existing shower door holes.

The vertical opening should be a minimum of 64-1/2" (1638 mm) to allow for installation clearance.

