## T418620N08



## Design By -

Ernesto Gismondi

#### Collection =

Outdoor



## Colors & Finishes =



## Materials =

- Body in aluminum
- Silicon-sealed silk-screened tempered glass
- Optical unit made of a PMMA lens and an anodized aluminum reflector


## Specifications ——

| Delivered lumens                   | 1753lm                |
|------------------------------------|-----------------------|
| Light output ratio                 | 62.61lm/W             |
| Power consumption                  | 28W                   |
| Led type                           | 27W C.O.B.*           |
| CCT (Correlated Color Temperature) | 4000K                 |
| CRI (Color Rendering Index)        | >80                   |
| Life expectancy                    | 50000Hrs              |
| Control type                       | On/Off                |
| Input Voltage                      | 120-277V              |
| Driver                             | ROAL - 1 x RSLD035-12 |
| BUG Rating                         | B2-U0-G0              |

#### Features & Accessories =

- Consists of an adjustable lighting unit and terminal board
- Rotation on base +/-180°, body tilting on bracket +/-130°, allowing accurate adjustment
- Positioning is maintained by means of locking dowels
- Electronic driver integrated
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

## Dimensions =




### Packaging =

1 Box

1 x 20" x 13-3/8" x 14-3/8" / 11.58 lbs - 50.7 cm x 33.7 cm x 36.3 cm / 5.252 kg

# Light distribution —

Direct



Luminaire weight —

8.26 lbs / 3.75 kg

Warranty —

5 year limited warranty

Red = Max Cd. Through Vertical plane
Blue = Max Cd. Through Horizontal plane

