

Teebaudo[®]

Nonskid Rug Underlay

WARRANTY AND CLEANING

TEEBAUD[®] is a multi-purpose non-skid rug underlay. The product is made of two different fibers needle punched together and coated with a water base, solvent free pressure sensitive dry adhesive. It can be used on wall-to-wall carpeting or on smooth flooring surfaces.

Prior to installing TEEBAUD[®], the floor should be vacuumed, clean and dry. TEEBAUD[®] must never be installed on a wet floor. In order to obtain a long lasting non-skid performance, avoid frequent removal and re-installation of TEEBAUD[®] from its designated installation area.

When installed on a smooth surface, TEEBAUD[®] may leave an inoffensive light residue made of dust, particles of dirt, fibers and resin. The residue can be easily cleaned with many common household cleaners, subject to specific floor finish/surface manufacturing guidelines.

Our recommendations for cleaning are as follows:

Wood floors (polyurethane finish)	-Orange GLO Hardwood Floor Everyday Cleaner -Bonakemy soap
Ceramic and vinyl floors	-General cleansers diluted with water
Natural stone with no sealant	-Mild soapy solution

TEEBAUD[®] is guaranteed not to mar, stain, oxidize or discolor properly installed, finished and maintained floors and carpeting.

TEEBAUD[®] is safe for use on radiant heated floors installed for residential application with temperatures not exceeding 90 degrees Fahrenheit.

Teebaudo[®]

Nonskid Rug Underlay

GUIDELINES

INSTALLATION INSTRUCTIONS

TEEBAUD[®] is a multi-purpose non-skid underlay pad. It can be used on wall-to-wall carpeting or on smooth flooring surfaces. In order to obtain maximum satisfaction and the best results with TEEBAUD[®], here are the suggested installation procedures:

RUG on wall-to-wall carpeting:

- Cut TEEBAUD[®] about 1"-3" smaller than the rug to be installed
- Remove the plastic release liner
- Place TEEBAUD[®]'s white side down, facing the wall-to-wall carpeting
- Then place the rug on top of TEEBAUD[®]'s gray side.

RUG on smooth flooring surface:

- Cut TEEBAUD[®] about 1"-3" smaller than the rug to be installed
- Remove the plastic release liner
- Place TEEBAUD[®]'s gray side down, facing the smooth floor
- Then place the rug on top of TEEBAUD[®]'s white side.

CUTTING

TEEBAUD[®] can be easily cut with scissors or a utility knife.

FLOOR PREPARATION

Prior to installing TEEBAUD[®], the floor should be vacuumed, clean and dry. Do not install TEEBAUD[®] on a wet floor. In order to obtain a long-lasting non-skid performance, avoid frequent removal and re-installation of TEEBAUD[®] from its designated installation area.

OVERSIZED RUGS

If several pieces of TEEBAUD[®] are necessary for one rug, simply apply as many pieces as needed, side-by-side. Taping or splicing is NOT necessary.

CLEANING

TEEBAUD[®] can be hand rinsed and air dried.

TEEBAUD[®], when installed on a smooth surface, may leave an inoffensive light residue which is water soluble. The residue can be cleaned with water or common household cleaners, such as Orange Glo Everyday Floor Cleaner for Hardwood Floors[™] or Bonakemy[™], subject to specific floor finish/surface manufacturing guidelines.