CORSO – model: PD-337 dwelLED[™]LED Pendant

WAC LIGHTING

Responsible Lighting®

			Fixture Type:
			Catalog Number:
			Project:
			Location:
4" 4" 126" 126" 4" PD-33718	4" 4" 32" PD-33732	4" 4" 4"	

— 43" — **PD-33743**

PRODUCT DESCRIPTION

A promenade of light delivered through a self illuminating halo within. A frosted acrylic diffuser conceals the high powered LEDs within the brushed aluminum spun metal shade. Corso is suspended on three thin low profile cables without the need for an additional power cord, lending to a simple and minimalistic design. Adjustable to different lengths through a push-pin locking mechanism at the canopy.

FEATURES

- Minimalist look with no visible power cord
- Even illumination with no hotspots
- Seamless brushed aluminum shade
- · Cable suspension carrying low voltage may be field shortened
- PD-33718 and PD-33743 are Title 24 Compliant
- Universal driver (120V-220V-277V)
- Color Temp: 3000K
- CRI: 80
- Dimming: 100% 5% ELV or 0-10V
- Rated Life: 83,000 hours
- Input: 120 277V

ORDER NUMBER

		Watt	LED Lumens	Delivered Lumens	Finis	sh
PD-33718	18"	22.5W	1495	940		
PD-33732	32"	88W	6340	4435	AL	Brushed Aluminum
PD-33743	43"	128W	11115	7300		

Example: PD-33732-AL

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

SPECIFICATIONS

Construction: Die cast Aluminum and Frosted Acrylic Diffuser

Light Source: High output LED.

Finish: Brushed Aluminum (AL)

Standards: ETL & cETL damp location listed. PD-33718 & PD-33743 are CEC Title 24 Compliant.