

### **Features**

- Dimmable LED task lighting
- Integrated touch sensor control with memory
- Energy efficient LED lighting 5000K
- 4100 Lumens
- CRI 90+
- Integrated Defogger

## Construction

- Quality polished edge mirror
- Single phase wire installation
- 5 MM Silver Backed Copper Free
- Installation Either Surface Mount
- (Side Mirror Trim Panels included) or Recessed
- Includes installation hardware

## **Codes/Standards Applicable**

- Conforms to UL Std. 962
- Cert. to CSA Std. C22.2 No.250.0-08
- ETL Intertek 5004931

### **Electrical System**

- 120Vac, 60Hz, 55W
- Electric Current: 0.45A
- Wattage: 55W

### Model

- SVANGE 4242R Right Swinging Door
- Included models in this configuration: Cabinet 1=1842L Cabinet 2=2442R



## **Electrical System**

- Perfomance Requirments: Contains the required
- Supervisory Circiut with the Auto-Monitoring Function as noted by UL 1310
- Input Voltage: Min 112Vac, Nom 125Vac, Max 137Vac
- Frequency:60Hz
- Front Receptacle Current: 102-132Vac Nominal 15A
- USB Output Current:5VDC Nominal 4A



## CABINET CONFIGURATION

 Included models in this configuration: Cabinet 1 = 1842L Cabinet 2=2442R





Kru

www.kruggusa



SURFACE MOUNT





Wall Cut Recess **Recessed Cabinet** C<sub>G.</sub> FRONT ВАСК D. E. Α. Optional Electrical Cord Outlets ] В. F. FRONT & BACKS MODEL А В С D Е G SVANGE4242R 40-1/2 42 42 18 24 39 3-7/8

**RECESSED MOUNT** 



## **RECESS INSTALLATION OPTIONAL ELECTRICAL CORD LOCATIONS**



#### ELECTRICAL CORD LOCATIONS

MODEL	MODEL A		С	D	
SVANGE4242R	1-1/2	1-1/8	1-3/8	11-1/4	







#### DOOR & CABINET

MODEL	А	В	С	D	E	F	G
SVANGE4242R	7/8	3-7/8	4-3/4	18	3/8	5-1/4	11-1/4



#### **INTERIOR CABINET**

MODEL	А	В	С	D	E	F	G	н	I	J
SVANGE4242R	3-3/4	5-5/8	1-1/4	38-1/4	2-1/4	22-1/2	16-1/2	2-3/8	3/8	3-5/8