


TR Series Angle Power Strip

Tamper Resistant Receptacles eliminate cutouts for receptacles and switches in your backsplash



Section Drawing



FEATURES

- Tamper Resistant
- · Easy Installation
- Designer finishes to blend with any decor
- 3-Year Limited Warranty
- Custom options include: USB Ports, Phone Jacks, Cable Jacks, Data Ports. See pg. 36 for more options.

APPLICATIONS

- Kitchens
- Baths
- Offices & Computer Labs
- Islands
- Shops & Garages

SPECIFICATIONS	
Construction Materials:	Powder Coated Aluminum
Input Voltage:	120V
Mounting:	Wood Screws & Wall Anchors
Wiring:	12 ga. Romex
Environment:	Dry Only
	_

TR SERIES ANGLE PO	OWER S	TRIP		
Part Number	Length	# of Duplex Recept.	Recept. Color	Finish
TR9-1ColorD-P-Finish	9"	1	B, G, W	BK, BZ, SN, WT
TR12-1ColorD-P-Finish	12"	1	B, G, W	BK, BZ, SN, WT
TR18-2ColorD-P-Finish	18"	2	B, G, W	BK, BZ, SN, WT
TR24-2ColorD-P-Finish	24"	2	B, G, W	BK, BZ, SN, WT
TR30-2ColorD-P-Finish	30"	2	B, G, W	BK, BZ, SN, WT
TR36-2ColorD-P-Finish	36"	2	B, G, W	BK, BZ, SN, WT
TR42-3ColorD-P-Finish	42"	3	B, G, W	BK, BZ, SN, WT
TR48-3ColorD-P-Finish	48"	3	B, G, W	BK, BZ, SN, WT
TR60-4ColorD-P-Finish	60"	4	B, G, W	BK, BZ, SN, WT
TR72-4ColorD-P-Finish	72"	4	B, G, W	BK, BZ, SN, WT

FINISHES









RECEPTACLE COLORS







Black (B)

Gray (G)

White (W)

OPTIONAL INSTALLATION COMPONENTS					
PART NUMBER	DIMENSIONS	DESCRIPTION			
TR-SQ-JB-P-Finish	3" x 3" x 21/8"	Square Junction Box			








TR Series Angle Power Strip

Tamper Resistant Receptacles eliminate cutouts for receptacles and switches in your backsplash

TR72-4ColorD-Finish




TR60-4ColorD-Finish




TR48-3ColorD-Finish




TR42-3ColorD-Finish




TR36-2ColorD-Finish



TR30-2ColorD-Finish




TR24-2ColorD-Finish



TR18-2ColorD-Finish



TR12-1ColorD-Finish



TR9-1ColorD-Finish



LEGEND





CUSTOM OPTIONS

- Custom lengths from 7" 92" (larger sizes will have a seam when assembled)
- Additional devices (see next page)
- · Custom device placement

CUSTOM OPTION DETAILS

- Receptacles must be a minimum of 5" apart (on center)
- Receptacles must be a minimum of 3" from end
- Custom charges will apply, call for a quote and assistance with your custom order
- Call for lead time



