

PARTS & ASSEMBLY SHEET

Fixture Name: Waverly 3500-SF AB

This fixture assembled PO:	Date:
----------------------------	-------

Notice: Please review the parts listing and check for all parts before assembling the fixture. If any parts are missing or damaged, please note on this sheet and contact the place of purchase to arrange for replacement parts.


DA DOC I	TCM	Company Name:		Co. Account #:		
PARTS LIST		to be filled out by retailer				
Mounting strap (circular)		Wire connectors		Deco nut		
1ea D4"		3ea P3 Orange		2ea 12mm		
Canopy		Junction box screw		Top loop		
1ea D6"X1"		2ea 8/32" x 1"	٧	1ea D50 x 60mm	~	
Chain		Mounting screw	(11111111111111111111111111111111111111	Canopy loop with Collar		
1ea 6ft x3.8mm		2ea 8/32" x 1-1/4"		1ea @3/8 x 40mm x	5mm	
Chain connector		Hex nut		Nipple		
2ea @3X38mm	9	2ea @3/8 x 3mm		1ea @3/8 x 65mm		
Mounting strap w/ ground screw		Screw				
1ea 3/4"X4"		2ea @8/32" x 8mm				
Part Needed				Quantity		
Part Needed				Quantity		
Reason why Comments	(missing, scratc	hed, broken glass, b	ent, bad finish)			
Reason why	(missing, scratc	hed, broken glass, b	pent, bad finish)			

FIXTURE ASSEMBLY INSTRUCTIONS

Read and review installation instruction sheet before assembling the fixture.

- 1. Place shade (Q) Thread the threaded pipe/stem (P) into the coupling at center of fixture body (R).
- 2. Thread the top loop (J) onto the stem (P1)and(P). Hand-tighten until the Top Loop is snug.
- 3. Install the light bulbs in accordance with the fixture's specifications.

(DO NOT EXCEED MAXIMUM WATTAGE RATING)



3500-SF AB

For Customer Service, contact the place of purchase to arrange for replacement parts.

PARTS & ASSEMBLY SHEET

Fixture Name: Waverly 3500-SF AB


ASSEMBLING THE FIXTURE as Chain hung (Fig.2)

- 1. Place Shade (Q) onto the threads of Threaded Stem (P) into the coupling at center of Fixture Body (R).
- 2. Thread the Top Loop (J) onto the Threaded Stem (P1)and(P). Hand-tighten until the Top Loop is snug.
- 3. Measure to determine the correct number of links needed for proper hanging height. Use a pair of pliers to open one link of Chain (K). Then remove and discard the excess chain.
- 4. Use Chain Connector (L) to attach one end of the chain to Top Loop (J) and close the chain connector.
- 5. Feed the fixture wires through the chain (every three links) and pull the wires until taut.
- 6. Slip Canopy Loop Collar (H) over the chain, then do the same with the Canopy (G).
- 9. To complete the installation, use the other chain connector to attach the other end of the chain to the Canopy Loop (F) and close the chain connector.
- 10. Make sure that the weight of the chandelier will be supported by the chain, not the electrical wire.
 - * You may now install the fixture.

Note: Complete these remaining steps after the fixture is hung.

11. Install the light bulbs (not provided) in accordance with the fixture's specifications.

(DO NOT EXCEED MAXIMUM WATTAGE RATING)



For Customer Service, contact the place of purchase to arrange for replacement parts.