

### Project:

Fixture Type:

Location:

Contact:

Images:

# **One-light Pendant**

Ceiling cord mounted • Damp location listed PROGRESS LED

# **Description:**

P500276-028-30

Provide a dramatic achitectural lighting design to any space with this LED pendant. A smooth metal beam with a satin white finish suspends from the ceiling to add clean visual interest to minimalist residential or commercial settings. The frame holds a polycarbonate shade in place to complete the design.

# **Specifications:**

- Satin White (-028) (Painted)
- Aluminum and steel Construction .
- . Polycarbonate Polycarbonate Diffuser
- The frame holds a polycarbonate shade in place to complete the design. .
- · A smooth metal beam with a satin white finish suspends from the ceiling to add clean visual interest to minimalist residential or commercial settings.
- · Provide a dramatic achitectural lighting design to any space.
- · Ideal for any hallway, foyer, kitchen, or dining room.
- Perfect for transitional, modern, or contemporary settings. •
- Measures 47-1/4-inch width by 1-3/8-inch height. •
- Uses one LED bulb that is included (39w max). •
- Able to be fully dimmable with dimmable bulbs. .
- · Includes installation instructions and mounting hardware.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality. .
- Canopy covers a standard 4" octagonal recessed outlet box •
- Mounting Backplate for outlet box included •
- 108" of wire supplied •
- Meets California Title 24 JA8-2016

# **Performance:**

		Longent
Number of Modules	1	Height: 1 Overall F
Input Power	39w	
Input Voltage	120 V	
Input Frequency	60 Hz	NG 1.1
Lumens/LPW (Delivered)	2900/74 (LM-79)	Width: 41 Height: c
CCT	3000 K	
CRI	90 CRI	
Life (hours)	50,000 (L70/TM-21)	
FCC	FCC Title 47, Part 15, Class B	
Min. Start Temp	-30 °C	
Warranty	5-year limited warranty	
Labels	cETLus Damp location listed	
	Meets California Title 24 JA8-2016	



#### **Dimensions:**

Width: 47-1/4" Depth: 1-3/4" Length: 47-1/4" 1-3/8" Ht. W/Wire: 113"

46.4325" 0-1/16"



# **One-light Pendant**

Ceiling cord mounted • Damp location listed PROGRESS LED

# P500276-028-30

### **Dimming Notes:**

P500276 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

# **Dimming Controls**

Leviton 6672

Lutron NTEVL-300

Lutron DVELV-300P

Lutron DVCL-253P

Lutron Caseta Wireless

Lutron AYCL-153P

Lutron TGCL-153-PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.