SPECIFICATION

Customer Service: 1-800-460-7019

www.fluidfaucets.com



Specifications

- Heavy brass construction for durability and reliability
- Kerox ceramic cartridge ensures life long trouble free service
- Single lever handle operation allows both volume and temperature control
- SSi Eco-Care pivot aerator 1.5 gpm (5.7 lpm) at 60 psi
- SSi "Speed Connector" for easy spout installation
- Single cover plate trim available
- Available waste pop-up drain
- Must be used together with the valve body F3100B for horizontal installation or with F3101B for vertical installation
- Used as wall mounted tub filler when flow straightener is used in lieu of aerator (F16008T-S with flow straightener)

Finish

- CP (Polished Chrome)
- PVD-BN (PVD Brushed Nickel)

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- NSF61-9
- ADA
- IAPMO / cUPC Listed
- **EPA Watersense Listed**
- AB1953 California Lead Plumbing Law Certified

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Quad Series Single Lever **Wall Mounted Faucet Model: F16008T**

























Model: F16008T