# Model: H/L/J-LED208

### AC LED Track Luminaire

# WAC LIGHTING

Responsible Lighting®

	Fixture Type:
7" 25%"	Catalog Number:
	Project:
	Location:

#### **PRODUCT DESCRIPTION**

LED208 track luminaire offers driverless AC LED technology and easy change of beam angles in field. Superior light output in a small, unobtrusive design. The high output LEDs outperform halogen 50W MR16. Developed for upscale residential and commercial environments.

**BEAMSHIFT™ TECHNOLOGY** 

Flood 40° Configuration

#### FEATURES

- · Driverless AC LED technology
- Compact integrated design
- · Easy change of beam angles in field
- Outperforms halogen 50W MR16
- · Consistent high quality beam pattern
- · Accommodates 1 lens accessory
- · 360° horizontal and 90° vertical aiming
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

#### **SPECIFICATIONS**

Construction:	Die-cast aluminum with removable PC lens cap
	for easy change of lenses or accessories
Finish:	Antique Bronze (AB)
Driver:	Input voltage: 120VAC 50/60Hz.
Light Source:	High Voltage AC LED module.
Dimming:	Dims to 10%-100% with electronic low voltage (ELV) dimmer. Compatible with LUTRON SELV-300P, DVELV-300P

Standards: ETL & cETL Listed. Energy Star Rated.





LED208 track luminaires come with BeamShift<sup>™</sup>, allowing in-field change of beam angle

simply by changing the location of the lens with a simple flat-head screwdriver.

Spot 25° Configuration Convex Lens located behind the spacer Convex Lens located in front of the spacer.

RDERN	IUMBER	1										FINISHES
Track Sy	stem	Model		Finish	Voltage	Color Temp	Power	CRI	Beam	Lumens	Efficacy	AB
	rack rack	LED208-30	AB	Antique	120V	3000K	15W	85 —	25°	505	33.7 Lm/W	
	Track	LED208-30	AD	Bronze	1200	3000K	1277	65	40°	640	42.7 Lm/W	
								· ·				
	16	2 2020	20					LENSES &	& ACCES	SORIES		
[	LE	D208-3	0	]-[				LENSES &	& ACCES	SORIES Colo	r	
		<b>D208–3</b> 08-30-AB	0	]-[					& ACCES	Colo AMB	Amber	
			0	]-[				Model		Colo AMB BLU	Amber Blue	
			0	]-[						Colo AMB BLU	Amber Blue Green	

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

# Model: H/L/J-LED208

### AC LED Track Luminaire



Responsible Lighting®

**APPLICATION PERFORMANCE - 3000K** 

0° Aiming Angle (ceiling to floor)

	LI	ED208-3	30		LED208-30			
		25° bean	า		40° beam			
Distance	FC	L	W		FC	L	W	
4 ft	80	1.8	1.8		67	2.9	2.9	
6 ft	35	2.7	2.7		30	4.4	4.4	
8 ft	20	3.5	3.5		17	5.8	5.8	
10 ft	13	4.4	4.4		11	7.3	7.3	

45° Aiming Angle (ceiling to wall)

	_	ED208-3			<b>LED208-30</b> 40° beam			
Distance		25° bean	-	1		40 Dearr		
Distance	FC	L	W		FC	L	W	
4 ft	28	3.7	2.5		24	6.7	4.1	
6 ft	13	5.6	3.8		11	10.1	6.2	
8 ft	7	7.5	5.0		6	13.4	8.2	
10 ft	5	9.3	6.3	]	4	16.8	10.3	

PHOTOMETRY



Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585