# SYMMONS<sup>®</sup> Temptrol<sup>®</sup>



# PRESSURE BALANCING TUB/SHOWER VALVE BODY SPECIFICATION SUBMITTAL

## MODEL NUMBERS

#### 262XBODY

Pressure Balancing tub/shower valve body **162XBODY** 

Pressure Balancing tub/shower valve body pressure testing cap

### FEATURE HIGHLIGHTS

- Brass, bronze and stainless steel construction
- Pressure balancing mixing valve to maintain safe shower temperature
- Adjustable stop screw to control maximum hot water temperature to valve
- Integral service stops allow water shut-off for valve servicing
- 4 port valve body in common plane
- Inlets: 1/2" IPS and 1/2" sweat
- Outlets: 1/2" IPS and 1/2" sweat
- Accommodates back to back installations
- Accommodates thin wall installations
- Stringer mounts included

### **OPTIONS/MODIFICATIONS**

-CHKS Integral check stops for use in installations where a positive shut-off device is used downstream of valve
-RV Reverse seat for back to back installations

### **INLET/OUTLET ADAPTERS**

- □ -CP CPVC fittings
- -P1 PEX crimp fittings
- -P2 PEX expansion fittings

Buy American Act Compliant

#### COMPLIANCE

- ASME A112.18.1/CSA B125.1
- ASSE 1016



### WARRANTY

**Limited Lifetime** - to the original end purchaser in consumer installations.

**5 Years** - for commercial installations.

Refer to www.symmons.com/warranty for complete warranty information.





