## Tetragono 90 floor T417200W08

# SPECIFICATIONS

ĺ	Design By Ernesto Gismondi	Specifications Delivered lumens Light output ratio	504lm 34.52lm/W
	Collection	Power consumption	14.6W
	Outdoor	Led type	12W Array*
		CCT (Correlated Color Temperature)	3000K
	(ID) r(M)w (P65)	CRI (Color Rendering Index)	>80
		Life expectancy	50000Hrs
		Control type	On/Off
Colors & Finishes		Input Voltage	120V
Anthracite grey		Driver	MEAN WELL - 1 x APC-16-350
		BUG Rating	B0-U2-G0

## Materials =

- Lamp support in painted extruded aluminum
- Base in painted steel
- Lighting unit in die-cast aluminum
- Reflectors in metallic polycarbonate
- UV resistant diffuser in shock resistant polycarbonate

#### Features & Accessories

- Base contains holes for floor installation by means of log bolts and dowels
- Provided with cable and IP67 connector

• Electronic driver integrated

- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

## Dimensions -



### Light distribution

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane Luminaire weight

Warranty 5 year limited warranty Packaging =

1 Box

1 x 11-1/8" x 7-3/8" x 45-3/4" / 15.54 lbs - 28 cm x 18.5 cm x 116 cm / 7.05 kg

