

ELKAY®

Installation Manual

EF1500VRBC

1500 Gallon Vandal-Resistant Retro-Fit Filter Kit

IMPORTANT NOTE – To avoid danger of an electric shock hazard, disconnect power to your unit before installing the filter.

IMPORTANT

**THIS IS AN INDOOR APPLICATION ONLY.
ALL SERVICE TO BE PERFORMED BY AN
AUTHORIZED SERVICE PERSON.**

TOOLS REQUIRED

BUT NOT PROVIDED:

- SAFETY GLASSES
- GLOVES
- LEVEL
- PENCIL
- MOUNTING SCREWS, ANCHORS, FASTENERS

INSTALLATION STEPS

1. Before starting your installation, verify that you have the following included pieces.
 - a. 1 Pinned Torx Bit
 - b. 1 Pinned Torx Screw
2. Find a location to mount your new filter box near the water dispenser to which it is being connected. For accurate monitoring, the filter box should be mounted vertically as shown (Fig. 2, page 2).
3. **Shut off the water and electricity to the water dispenser.**
4. Remove the front cover by lifting the cover at the bottom and slide upwards toward the top.



Fig. 1

5. Take the filter box and place on the wall in the desired location. Making sure that it is level, take a pencil and mark around the inside opening and the mounting locations. If the water will not be coming thru the wall into the back of the filter box, knock-outs have been provided to allow the water lines to run thru the sides or bottom. **NOTE:** If running the water lines thru the knockouts, use the appropriate protection (not provided) to keep the lines from getting cut.



Fig. 2




Fig. 3

6. Cut a hole in the wall anywhere inside the marked location to allow room for the water lines to come into the back of the box.
7. Remove any protective covering from the outside of the filter box.



Fig. 4



Fig. 5

8. Using the appropriate fasteners (Not Supplied), mount the box to the wall.

9. Disconnect the water inlet to the water dispenser and connect to the inlet copper tube on the filter head.




Fig. 6

10. Connect the poly tubing from the outlet of the filter head to the inlet of the water dispenser.



Fig. 7

11. Remove the red cap from the filter and install on the filter head turning clockwise.



Fig. 8

12. Turn on the water and check for leaks. Repair as needed.
13. Run approximately 1 gallon of water through the water dispenser. This flushing procedure purges air and fine carbon particles from the filter. After 1 gallon of water has been purged, carefully inspect all water connections for leaks.

14. After peeling the protective covering from the front cover, hook the tabs on the top into the slots on the top of the box. Slide the cover down and install the supplied screw. Once done keep the bit as it will be needed for replacing the filter.



Fig. 9



Fig. 10

NOTICE

To receive maximum benefit from your ELKAY WaterSentry® filters, note the installation dates below and change according to the following guidelines.

ELKAY Part No. 51299C WaterSentry® VII -- Lead Reduction Filter

Change every 1,500 gallons, or once a year -- whichever occurs first.

-- KEEP THIS SHEET IN A HANDY LOCATION --

DATE INSTALLED	MODEL (TYPE OF FILTER)	SERVICE PERSON	DATE INSTALLED	MODEL (TYPE OF FILTER)	SERVICE PERSON

FOR REPLACEMENT FILTER, PLEASE CALL 1.800.834.4816
ELKAY MANUFACTURING COMPANY • 2222 CAMDEN COURT • OAK BROOK, IL 60523 • 630.574.8484
www.Elkay.com