ASSEMBLY INSTRUCTIONS

NOTE TO CUSTOMERS:

- For ease and speed of assembly we recommend that before you commence each step of the assembly that you identify all the parts required to complete that step.
- We recommend that where possible you allow sufficient space to assemble the item as close as possible to the place where it will be once assembled.
- For the protection of your furniture we recommend that the product is placed on protected surfaces during assembly to prevent any damage.
- During assembly do not over tighten, as this may damage the product.
- Please ensure you retain all the product packaging until the item completely assembled.
- Please periodically check all fittings and re-tighten as necessary.
- Please never allow any liquids to remain on your furniture as absorption can cause the wood to warp or the finish to de-laminate.
- It is recommended that this item should be assembled by two adults.

To insert a cam lock: (Please read below instructions before assembling)



- 3. When inserting the cam lock make sure the arrow of the cam lock faces the cam screw.
 - 4. To tighten the cam lock turn the cam lock clockwise 90-180 degree or until the arrow is facing opposite the place cam lock was inserted.

NOTE: DO NOT USE AN AUTOMATIC SCREWDRIVER TO TIGHTEN CAM LOCKS.

Note:

• Read these instructions carefully before assembling.

- Tools required : Phillips screwdriver, flat screwdriver.
- Find a clean, smooth area on which to work, such as a carpet, in order to avoid scratching the wood surfaces.
- Wait to dispose of the packing material until assembly is complete and all parts and hardware are accounted for.
- Two or more people might be required for assembly.





1): Attach Stopper D to Top Support Bar A5 with included screw.

- 2): Attach Magnet C to Middle Support Bar A6 with included screws.
- 3): Assemble Support Bars A5 & A6 to Side Panels A2 & A3 using Camlocks A and Wood Dowels B.



Page 5 of 9







- 1): Insert Pin K into the hole on the bottom of Right Door A13, Then connect Right Door A13 to Bottom Panel A7 as below Fig.2. Insert Pin K into to hole on the top of Right Door A13, then press down Pin K see Fig.3. and hold the door panel carefully into the cabinet with the upper pin poping up into the hole of Top Support Bar A6.
- 2): Repeat the above step to assemble Left Door A12.
- 3): Assemble Knobs I to Doors A12 & A13 with included bolts.

