

KENT™ 6032 LH ADA

Always check the website for the most updated specifications: www.americh.com











All bathtub dimensions are $\pm 1/2$ ".

Builder Series







DIMENSIONS

60" x 32" x 18" (1524 x 813 x 457 mm) Whirlpool Operating Gallons = 20 (Liters = 76) Gallon to Overflow = 50 (Liters = 189)

MATERIAL: Acrylic (All Americh Standard Colors)

TUB FLOOR: Textured

UNDERMOUNT: No

Platinum Series

N/A

Combination

(pump and blower location only)



ELECTRICAL REQUIREMENTS

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.


STANDARD EQUIPMENT:

- Apron
- Molded Tile Flange
- Adjustable feet









OPTIONAL ACCESSORIES

- Chromatherapy
- Grab Bars: 9" 14" 16"
- High Density Insulation
- iBath Sound System
- Inline Heater (whirlpool only)
- Jets: Additional or Rotary
- Ozone System (whirlpool and/or Airbath only)
- Pillows: 12" Angle
- Remote Control Upgrade (select series only)
- Thermal Comfort System (TCS cannot be used with VSM)
- Trim Kit Upgrade
- Vibro Sonic Massage (VSM cannot be used with TCS)
- Waste & Overflows Upgrades
 - Cable Drive Waste & Overflow
 - PVC Waste & Overflow⁺
 - Linear Waste & Overflow

(+) Standard on Luxury Series

INSTALLATION TIPS

- Install according to Owner's Manual and local codes.
- Airbath III units may be 11/2" 21/2" higher than stated.
- Any whirlpool or Airbath-unit requires an access panel.
- Hot water supply should be 65-75% of tub capacity or greater.
- Always consult your local plumber for recommendations as installations will vary.
- The combination of multiple systems and options may require components to stick out and/or be remotely installed in the field.

CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1 ANSI A112-19.7
- ANSI A112.19.8

Contact Americh for additional approvals.

