SILO X10 – model: 2010

H/L/J Track Luminaire

WAC LIGHTING

Responsible Lighting®

Fixture Type:
Catalog Number:
Project:
Location:
7½8" 5"

PRODUCT DESCRIPTION

Silo offers superior light output in a small, sleek design. Engineered synthesis of driver, single point source LED, optical and thermal management in a slender diecast housing. Ideal for residential, retail and lower mounting height commercial applications.

FEATURES	SPECIFICATIONS			
 35° TIR lens pre-installed. 25° TIR lens included Integral driver and high output COB LED 	Construction:	Die-cast aluminum with removable front cap for lenses or accessories		
Outperforms halogen 65W MR16	Input:	120VAC 50/60Hz		
 Accommodates one flat lens accessory or one glare control accessory 350° horizontal and 90° vertical aiming 	Power:	10W		
50,000 hour rated life	Light Source:	High output COB LED		
5 year WAC Lighting product warranty	Dimming:	100%-5% electronic low voltage (ELV) dimmer		
	Standards:	UL & cUL Listed, Energy Star®		
	Finish:	Powder coated Black and White. Anodized Brushed Nickel and Brushed Brass		

ORDER NUMBER

Track	Model	Beam	Lumens	CBCP	Color Tem	р	CRI	Finish		
H H Track L L Track J J/J2 Track	2010	25° 35°	790 790	2575 1545	930 30	000K	90	BK BN BR WT	Black Brushed Nickel Brushed Brass White	

_-2010-930-___

Example: H-2010-930-BK

FLAT LENS		FLAT LENS		GLARE CONTROL		
Amber Blue Green Red Yellow	LENS-11-AMB LENS-11-BLU LENS-11-GRN LENS-11-RED LENS-11-YEL	Frosted Spread Beam elongating	LENS-11-FR LENS-11-SPR LENS-11-BEL	Cross louver - Black Cross louver - Brushed Nickel Cross louver - White Snoot - Black Snoot - Brushed Snoot - White	LENS-11P-CRL-BK LENS-11P-CRL-BN LENS-11P-CRL-WT LENS-11-SNOOT-BK LENS-11-SNOOT-BN LENS-11-SNOOT-WT	

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

1