

Indoor

AirPro

Ceiling Fans

-80

-81

52" 5 Blade Fan

ENERGY STAR[®] Qualified Type

-09CH

-09WA -20 -77

-09 P2521

	Catalog	Brushed	Brushed Nickel	Brushed Nickel	Antique Bronze	Forged Bronze	Forged Black	Antique Nickel	Dimensions (Inches)			
	No.	Nickel							Α	В	С	D
	P2521	-09	-09CH	-09WA	-20	-77	-80	-81	52	14-5/8	11-9/16"	11-3/4
		White/	Cherry/	Classic	Classic	Classic	Dark	Medium			CTC	
		Natural	Natural	Walnut/	Walnut/	Walnut/	Walnut/	Oak/				
		Cherry	Cherry	Medium	Medium	Medium	Dark	Cherry				
		blades	blades	Cherry	Cherry	Cherry	Cherry	blades				
				blades	blades	blades	blades					
B V				P							D	

Specifications:

General

IDE

Airflow

3,094

Cubic Feet Per Minute

The higher the airflow, the more air the fan will move

Airflow Efficiency: 78 Cut Feet Per Minute Per Wat

(GU

ENERG

Estimated

Yearly Energy Cost

Cost Range of Similar Models (19" - 84")

Based on 12 cents per kWh and 6.4 hours use per
Your cost depends on rates and use
Energy Use: 39 Watts

Fan mounted as close-to-ceiling.

\$34

\$1 1

\$3

- ENERGY STAR[®] qualified
- 30 year limited warranty
- **Blades**
 - Five blades
 - Reversible
 - 12 degree pitch

Finish

- Sure Connect blade attachment system
 - Screws preinstalled in blades for • attachment to motor arms
 - Special guides align blades to motor arms
 - Preinstalled rubber isolation pads minimize vibration noise
- Plywood blade construction

Motor

- Triple capacitor speed control; manual reverse control
- 153mm dia x 18mm high
- Pull chain on Brushed Nickel (-09) is chrome with a white fob and Antique Nickel (-81) is antique brass with a black fob, and all the rest have antique brass chains with walnut fob's.

ENERGY INFORMATION AT HIGH SPEED

AIRFLOW:	4306 CFM cubic feet per minute				
ELECTRICITY USE:	65 watts (excludes lights)				
AIRFLOW EFFICIENCY:	66 cubic feet per minute per watt				
Fan on a downrod					

Mounting

- Dual ceiling mounting use with downrod or install close to ceiling
- Quick Install canopy
 - Installs without removing J-box screws
 - Holds fan for wiring during installation
 - Dual-mount for downrod or close to • ceiling mounting
- A 3/4" x 4-1/2" downrod is included. Longer accessory downrods can be ordered separately
- Standard canopy designed for sloped ceilings up to 45 degrees (12:12 ceiling pitch)
- Oversized, textured die cast hanger ball reduces noise and wobble vibrations
- Canopy covers standard recessed 4" octagonal outlet box. Note: An outlet box assembly designed for fan installation is required (not included)
- Mounting hardware is included

Electrical

- 80" lead wires included
- Prewired

Labeling

CUL listed

www.progresslighting.com

Progress Lighting

29607

701 Milliennium Blvd. Greenville, South Carolina

Fan on a downrod.