

One-Light Outdoor

 Wall mounted • Wet location listed **PROGRESS LED**


Description:

Arrive LED lanterns feature a die-cast aluminum, powder coated frame and heavily textured glass. One-light extra-large wall lantern. 90+ CRI, 3000K, 1,211 lumens 71.2 lumens/watt per module (source). Energy Star.

Specifications:

- Black (-31) (painted)
- Die-cast aluminum Construction
- Clear Seeded glass panels
- LED Module is replaceable (part # 93053641)
- Die-cast aluminum, powder coated frame.
- Heavily textured glass.
- 90+ CRI, 3000K, Energy Star.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1211/71.2 (LM-82)
Lumens/LPW (Delivered)	824/49.3 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements

for outdoor use only

P6076-3130K9

Images:



Dimensions:

Width: 11"
Depth: 12-1/4"
Height: 16"
H/CTR: 8-5/8"

Glass
Width: 0-1/8"
Length: 7-5/8"
Height: 11-5/16"



Photometrics:

P6076-3130K9

ELECTRICAL DATA	P6069-3130K9
Input Voltage	120 V
Input Frequency	60 Hz
Input Current	0.142 A
Input Power	17
Power Factor	Greater than 0.90
THD	<20%
FCC	Meets FCC Title 47, Part 15 Class B
Operating Temperature	-30 °C to 30 °C
Dimming	Yes*

*See Dimming Notes for more information

P6076-3130K9

Dimming Notes:

P6076 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vieri VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.