TLM2102



Design By

Michele De Lucchi Giancarlo Fassina

Collection =

Design

(ll) us	(IP:

Colors & Finishes =

	Parchment (Diffuser)
1/4	Aluminum (Body & Base)

Materials =

- Arm structure in extruded aluminum
- Joints and tension control knobs in polished die-cast aluminum
- Tension cables in stainless steel
- Floor support stem in extruded aluminum
- Weighted steel base with stamped aluminum


Specifications =

Delivered lumens	1918lm
Light output ratio	61.87lm/W
Power consumption	31W
Led type	31W C.O.B.*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	DIMMABLE (On Cord)
Input Voltage	120V
Driver	N/A

Features & Accessories =

- Fully adjustable articulated arm structure
- Interchangeable plug options accommodate most countries electrical outlets


Dimensions •





Light distribution

Diffused



Warranty =

5 year limited warranty

77.61 lbs / 35.2 kg

Packaging •

4 Boxes

1 x 13-11/16" x 7-15/16" x 44-3/16" / 6.39 lbs - 34.5 cm x 20 cm x 112 cm / 2.9 kg

1 x 19-3/8" x 19-3/8" x 13" / 1.1 lbs - 49 cm x 49 cm x 33 cm / .5 kg

1 x 16-1/4" x 16-1/4" x 4-13/16" / 37.92 lbs - 41 cm x 41 cm x 12 cm / 17.2 kg 1 x 16-1/4" x 16-1/4" x 4-13/16" / 38.36 lbs - 41 cm x 41 cm x 12 cm / 17.4 kg

Luminaire weight

Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane