
800LPH SOLAR MODEL: SLP 108 READ AND SAVE THESE INSTRUCTIONS ASSEMBLY INSTRUCTIONS PUMP KII

PARTS: UNPACK THE PACKAGE
YOU SHOULD HAVE RECEIVED THE FOLLOWING


1PC PUMP,
1PC SOLAR PANEL,
1SET FOUNTAIN NOZZLES
1PC SOLAR PANEL BRACKET,
2PC EXTENSION TUBES
1PC GROUND SPIKE. 12PC 15ET

TO PROTECT THE PRODUCT, PLACE ALL PARTS ON A SOFT SURFACE BEFORE ASSEMBLY.


SPIKE TOGETHER, THEN ATTACH BRACKET TO BACK OF THE SOLAR PANEL FRAME AS SHOWN 1. JOIN BRACKET, EXTENSION TUBES AND



THE SOLAR PANEL TO FACE SUN WHEN SUN IS AT ITS HIGHEST POINT. ENSURE THE POSSIBLE TO MAKE THE MOST OF THE DAYLIGHT HOURS. IT IS IMPORTANT TO ANGLE SHRUBS OR BUILDINGS SOLAR PANEL IS NOT SHADED BY TREES (In Northern Hemisphere) AS MUCH AS POSITION THE SOLAR PANEL TO FACE SOUTH 2. INSERT THE SPIKE INTO THE GROUND.



3. TWIST PUMP PLUG SLIGHTLY AND PUSHING SUNLIGHT. WORK WHEN SOLAR PANEL RECEIVE GOOD GROOVES. YOUR SOLAR PUMP WILL BEGIN TO SURE THE CONNECTOR SEALS ARE FULLY IN IT INTO THE HOLE FOR PUMP PLUG, MAKE



SLP108 INSTRUCTIONS (PAGE 1 / 2)

01/2015


READ AND SAVE THESE INSTRUCTIONS OPERATING INSTRUCTIONS 800LPH SOLAR MODEL: SLP 108 PUMP

4. SOLAR PUMP FUNCTIONS

THIS PUMP RUNS FROM DIRECT SUNLIGHT, PUMP PERFORMANCE IS DIRECTLY RELATED TO THE AMOUNT AND STRENGTH OF SUNLIGHT RECEIVED BY SOLAR PANEL. THIS SOLAR PUMP IS DESIGNED PRIMARILY TO OPERATE IN SUMMER MONTHS BUT ALSO WORK IN SPRING AND AUTUMN PROVIDED THERE IS GOOD SUNSHINE.

MAINTENANCE OF PUMP

IF YOU FIND THE PUMP START LOSING POWER OR STOP WORKING, CHECK THE PUMP FILTER AND IMPELLER BLOCKED, CLEAR THEM WITH WATER.



1 PUMP CASE 2 IMPELLER COVER

③ IMPELLER ④ PUMP ⑤ FILTER

TROUBLE SHOOTING

CHECK SOLAR PANEL, PUMP CONNECTED WELL.

CHECK SOLAR PANEL CORRECTLY POSITIONED IN SUNNY PLACE, ENSURE THE SOLAR PANEL IS NOT SHADED BY TREES, SHRUBS OR BUILDINGS.

CHECK WATER LEVEL, MAKE SURE THE PUMP IS FULLY SUBMERGED.

CHECK THE FOUNTAIN TUBING FOR KINKS AND OBSTRUCTIONS.

CHECK THE PUMP IMPELLER BLOCKED BY DEBRIS

ON/OFF THE PUMP SEVERAL TIMES TO CLEAR ANY AIR THAT MAY HAVE BEEN TRAPPED. CHECK THE PUMP MAY BE "AIR LOCKED", TURN

7. TECHNICAL DATA

MAX. WATER LIFT: 200CM / 80"
MAX. FOUNTAIN HEIGHT: 110CM
WORKING FOULTAGE: DC15V-18V
WORKING POWER: 4.4W-6.3W
PROTECTION GRADE OF PUMP: IP68 MAX. WATER FLOW: 800 LPH

SOLAR PANEL: 8W-18V-0.444A
PANEL SIZE: 358X238X18 MM
PROTECTION GRADE OF PANEL: IP44

8. WINTER PROTECT

INDOOR STORAGE IS RECOMMENDED FOR THE WINTER IN HARSH CLIMATES.

9. WARRANTY

WWW SERENITYHEALTH COM/CONTACT-US/ ALSO EMAIL US VIA OUR CONTACT US PAGE AT: CUSTOMERSERVICE@SERENITYHEALTH.COM, OR YOU COULD FREE TO CONTACT US BY PHONE AT: 888-881-4668, BY EMAIL ANY QUESTIONS, COMMENTS OR CONCERNS PLEASE FEEL THANK YOU FOR CHOOSING SUNNYDAZE DÉCOR. IF YOU HAVE

DEFECT AND FOR FUTURE QUALITY CONTROL. WE WILL USE THE PHOTOS TO DETERMINE THE CAUSE OF PURCHASE AND PHOTOS OF THE DEFECTIVE MERCHANDISE PRODUCTS AT OUR DISCRETION WITHIN THE ONE YEAR ITEMS WE SELL. WE WILL SEND NEW PARTS, OR REPLACE WE STAND BEHIND OUR BRAND AND THE QUALITY OF THE TO PROVIDE PROOF OF PURCHASE WITH THE DATE OF WARRANTY PERIOD. BEFORE WE CAN HELP, YOU WILL NEED

