

ASSEMBLING & INSTALLATION INSTRUCTIONS PRODUCT# 8457-57 8458-57

For Ceiling Mount Fixtures

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .
ATTENTION! COUPER LE COURANT AU FUSIBLE OU LE DISJONCTEUR.

MOUNTING THE FIXTURE

1. Shut off the power at the fuse box or circuit breaker box. Remove the old fixture from ceiling, including the crossbar.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Thread the two Mounting Screws (A) about 1/4" into the pre-drilled holes in the Crossbar (B) spaced the same distance apart as the holes in the fixture (D) .
4. Attach the crossbar (B) to the outlet Box using the two screws (C) from the outlet Box. The side of the crossbar marked "GND" must face out.
5. Hold the fixture (D) towards the crossbar and connect the electrical wires as follows (See Fig.2). Connect the black wire from the fixture to the black house (hot) wire; connect the white wire from the fixture to the white house (neutral) wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Other wise attach the bare copper fixture wire to the green ground screw on the crossbar. Tuck the wire connections neatly into the ceiling junction box as you holding the fixture assembly toward the ceiling.
6. Finish mounting the fixture (D) by placing it over both Mounting screws (A) so that the screws protrude from the keyholes in the bottom of the fixture (D). Rotate the fixture (D) until the screw are seat in the slots of the keyholes and tighten it with a screwdriver.
7. Install the light bulbs in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
8. Thread pipe (F) into center coupling of the fixture (D) and tighten it with nut (E).
9. Put the glass shade (G) onto the fixture (D) and protruding the pipe (F) from the center hole of the glass shade.
10. Thread lock nut (H) onto pipe (F) , attach the finial base (I), and lock it securely with the finial (J).

Your installation is now complete. Return power to the junction box and test the fixture.

Fig.1





Fig.2



MIN 90°C SUPPLY CONDUCTORS

LIVEX®
 LIGHTING
 EST. 1993

DOC20141208458