

Imagine Area Rugs

Construction	Tufted, Pinpoint Saxony
Face Fiber	Stainmaster® Tactesse® BCF Nylon Type 6,6
Yarn Finish	Superba® Heatset
Stain Repel / Stain Resist / Soil Release	Lotus FX™ Fiber Shield with Teflon® Protectant
Antimicrobial	AlphaSan® AF Built-In Protection
Dye Method	Digital Millitron® Dye Injection
Tufted Face Weight	40 oz./yd ² (1,356.3 g/m ²)
Gauge	1/10 (39.4/10 cm)
Stitches	15.0/in (59.1/10 cm)
Tufts	150.0/in ² (2,328.5/100 cm ²)
Finished Pile Height	0.22 in (5.59 mm)
Average Density	6,545
Standard Backing	Synthetic Endura-Loc™
Rug Sizes	7'8" x 10'9"; 5'4" x 7'8"; 3'10" x 5'4"; 2'8" x 3'10"; 2'1" x 7'8"
Nominal Total Weight	74 oz./yd ² (2,509.1 g/m ²)
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258 or ASTM-E662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70)	Self-Extinguishing
Static Electricity (AATCC-134)	≤ 3.5 KV, Permanent Conductive Fiber
Recommended Traffic	Residential
Recommended Maintenance	Capture® Carpet and Fabric Care
Indoor Air Quality – CRI Green Label Plus™	GLP2860, Carpet Category 1Y

Design Copyright – Milliken & Company

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.
Copies of actual test results are available upon request.



Warranties:

- 2-Year Limited Manufacturing Defects – Milliken Warranty
- 2-Year Abrasive Wear – Stainmaster Warranty
- Lifetime Antistatic – Stainmaster Warranty