

TUBE - model: WS-W2605, WS-W2604

LED Wall Mount

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

A simple sconce with endless possibilities. This cylindrical wall luminaire delivers powerful lumen output, either upwards or downwards, or a combination of both, depending on the configuration and application. Built to last with die cast aluminum construction and designed with no visible hardware, this low profile highly versatile Tube is perfect for your exterior and interior lighting needs. Five handsome architectural finishes will complement nearly any décor.

FEATURES

- IP65 Rated, ETL & cETL Wet Location Listed
- Mounts up or down
- Die-Cast Aluminum Construction
- Universal Voltage Input (120V - 277V)
- Dimming: ELV (120V) or 0-10V

SPECIFICATIONS

Construction: Aluminum with etched glass.

Power: Integral driver in luminaire. 120V - 277V input.

Light Source: High output LED

Mounting: Mounts directly to junction box

Dimming: 0-10V Dimming: 100%-10%

ELV Dimming: 100%-15% (120V only)








Finish: Brushed Aluminum (AL), Black (BK), Bronze (BZ), Graphite (GH), White (WT)


Color Temp: 3000K

CRI: 90

Rated Life: 70,000 hours

Standards: IP65 Rated, ETL & cETL Wet Location Listed,
Dark Sky Friendly.

	Beam	Photometry	Voltage	Watt	Lumens	Finish
 Single Light 	33°		120V	16W	800	AL Brushed Aluminum BK Black BZ Bronze GH Graphite WT White 
 Double Light 	33°		120V - 277V	30W	1750	



Example: **WS-W2604-BZ**

waclighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760