




NESSA B-122

SINGLE HANDLE VESSEL BATHROOM FAUCET



RECOMMENDED ACCESSORIES

D-703G D-702N D-702C
POP-UP DRAINS

HANDLE TYPE

LEVER

NUMBER OF HANDLE

1

CARTRIDGE MODEL

PREMIUM CERAMIC VALVE

SIZE: 28mm
STYLE: REGULAR

CONTROL WATER TEMPERATURE

HOT AND COLD

FAUCET FINISH

CHROME (C)	MATTE BLACK (N)
MATTE BLACK WITH GOLD (NG)	GOLD (G)

PRODUCT DIMENSIONS

Faucet Height (in)	11 13/16"
Spout Height (in)	9"
Spout Reach (in)	6 3/8"

CONFIGURATION

1-HOLE 3-HOLES

INSTALLATION

DESIGNED FOR EASY INSTALLATION.
INSTALLATION INSTRUCTION INCLUDED IN THE BOX

MATERIAL

LEAD FREE SOLID BRASS

CUT OUT HOLE

33mm

DECK PLATE

NO INCLUDED.
REQUIRED FOR 3 HOLES INSTALLATION

WATER FLOW

1.5
WATER FLOW RATE (GPM)

WATERLINES MODEL

CONNECTIONS 3/8"

WARRANTY

This product is covered by a limited lifetime warranty. Consult our website for complete details.

PRODUCT CARE

- Wipe faucet with damp cloth and mild household cleanser.
- Dry with soft cloth to maintain original appearance.
- Remove hard water stains with 50/50 solution vinegar and water.
- If mineral deposits are too hard to remove, specially in the aerator, unscrew aerator by hand or with tool provided with faucet, soak aerator in 50/50 vinegar and water solution for several hours, rub your fingers and use a tooth brush to remove mineral deposits, place aerator back into original position.

STANDARDS COMPLIANCE

Slim Aerator




NESSA

B-122


ROBINET DE SALLE DE BAINS
À POIGNÉE UNIQUE



DIMENSIONS



ACCESSOIRES RECOMMANDÉS



D-703G D-702N D-702C
DRAINS POP-UP

TYPE DE POIGNÉE



LEVIER

NOMBRE DE POIGNÉE

1

MODÈLE DE CARTOUCHE

VALVE EN CÉRAMIQUE PREMIUM

TAILLE: 28mm
STYLE: RÉGULIER

CONTROLE DE TEMPERATURE DE L'EAU



FROID ET CHAUD

FINITION DU ROBINET



CHROME (C)



NOIR MAT (N)



NOIR MAT AVEC OR (NG)



OR (G)

DIMENSIONS DU PRODUIT

Hauteur du robinet (po)	11 1/2"
Hauteur du bec (po)	9"
Portée du bec (po)	6 3/8"

CONFIGURATION



1-TROU

3-TROUS

INSTALLATION



CONÇU POUR UNE INSTALLATION FACILE.
INSTRUCTIONS D'INSTALLATION INCLUSES DANS LA BOÎTE

MATÉRIEL



LAITON SOLIDE SANS PLOMB

TAILLE DE LA COUPE



PLAQUE DE PLATEAU

NON INCLUS.
REQUIS POUR UNE INSTALLATION À 3 TROUS

DÉBIT D'EAU

1.5
DÉBIT D'EAU (GPM)

MODÈLE DE FLOTTAISON



CONNEXIONS 3/8"

GARANTIE

Ce produit est couvert par une garantie à vie limitée. Consultez notre site internet pour obtenir tous les détails.

ENTRETIEN

- Essuyez le robinet avec un chiffon humide et un nettoyant ménager doux.
- Séchez avec un chiffon doux pour conserver l'apparence d'origine.
- Enlevez les taches d'eau calcaire avec un mélange de 50 % d'eau et 50 % de vinaigre.
- Si les dépôts de minéraux sont trop difficiles à enlever, spécialement dans l'aérateur, dévissez-le à la main ou à l'aide d'un outil fourni avec le robinet, trempez-le dans un mélange de 50 % d'eau et 50 % de vinaigre pendant plusieurs heures, utilisez une brosse à dents pour éliminer les dépôts de minéraux, et remplacez-le dans sa position originale.



NORMES CONFORMES



Slim
Aerator

Stylish International Inc.

www.stylishkb.com

[stylish.international.inc](https://www.instagram.com/stylish.international.inc)

care@stylishkb.com

+1-855-789-5352