

Always check the website for the most updated specifications: www.americh.com



Builder Series



Platinum Series



Airbath System II





LEGEND: PUMP BLOWER - JET ROTARY JET

GRAB BAR ACCESS PANEL (MINIMUM 16" X 20")

INSTALLATION TIPS

- Install according to Owner's Manual and local codes.
- \bullet Airbath III units may be $1^{1\!/}\!\!2''$ $2^{1\!/}\!2''$ higher than stated.
- Any whirlpool or Airbathunit requires an access panel.
- Hot water supply should be 65-75% of tub capacity or greater.
- Always consult your local plumber for recommendations as installations will vary.



• Cut-out dimensions: Americh recommends waiting until the actual unit is received.



Luxury Series



(pump and blower location only)



Airbath System III



Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

STANDARD EQUIPMENT:

- 59 -

All bathtub dimensions are $\pm 1/2''$

TUB FLOOR: Textured UNDERMOUNT: Yes

DIMENSIONS

42

126

69" diameter x 21" (1753 mm dia. x 533 mm) Whirlpool Operating Gallons = 70 (Liters = 265) Gallon to Overflow = 90 (Liters = 341)

MATERIAL: Acrylic (All Americh Standard Colors)

• Adjustable Feet

OPTIONAL ACCESSORIES

- Chromatherapy^{*}
- High Density Insulation*
- iBath Sound System
- Inline Heater (whirlpool only)
- Jets: Additional or Rotary*
- Lo Profile Tub Edge
- Ozone System (whirlpool and/or Airbath only)
- Pillows: 12" *
- Remote Control Upgrade (select series only)
- Serenity Soak (tub only)
- Syllent Pump with Heated Air*
- Trim Kit Upgrade*
- Waste & Overflows Upgrades
 - Cable Drive Waste & Overflow*
 - PVC Waste & Overflow⁺
- (*) Standard on Platinum Series
- (+) Standard on Luxury Series

CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1 ANSI A112-19.7
- ANSI A112.19.8

Contact Americh for additional approvals.