# T418640W08



## Design By -

Ernesto Gismondi

#### Collection =

Outdoor



# Colors & Finishes =



#### Materials =

- Body in aluminum
- Silicon-sealed silk-screened tempered glass
- Optical unit made of a PMMA lens and an anodized aluminum reflector


#### Specifications ——

Delivered lumens	1468lm
Light output ratio	52.43lm/W
Power consumption	28W
Led type	27W C.O.B.*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120-277V
Driver	ROAL - 1 x RSLD035-12
BUG Rating	B2-U0-G0

#### Features & Accessories

- Consists of an adjustable lighting unit and terminal board
- Rotation on base +/-180°, body tilting on bracket +/-130°, allowing accurate adjustment
- Positioning is maintained by means of locking dowels
- Electronic driver integrated
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

# Dimensions =




## Packaging =

1 Box

1 x 20" x 13-3/8" x 14-3/8" / 11.58 lbs - 50.7 cm x 33.7 cm x 36.3 cm / 5.252 kg

# Light distribution —

Direct



Luminaire weight —

8.26 lbs / 3.75 kg

Warranty —

5 year limited warranty

Red = Max Cd. Through Vertical plane
Blue = Max Cd. Through Horizontal plane

