

Phase 2.1 LED

 Wall mounted • Damp location listed **PROGRESS LED**


P300209-009-30

Description:

Phase 2.1 features a thin, acrylic lens that provides even illumination. This specially designed 36in. linear bath fixture delivers ambient light to surfaces free of shadows. Phase 2.1 is a perfect addition to modern applications. An integrated LED source provides energy and cost savings benefits. Can be installed vertically or horizontally.

Specifications:

- Brushed Nickel (-009) (plated)
- Aluminum Construction
- White Acrylic diffuser
- The white acrylic shade provides even illumination
- Square end caps and back plate are finished in Brushed Nickel
- The LED light is diffused to create an even glow
- Ideal for residential, commercial and multi-family applications
- Mount horizontally or vertically on the wall in bath and vanity settings
- Measures 36in W x 4-3/4in ht.
- 34w integrated LED, 2,450 delivered lumens 72 lumens/watt, 3000K color temperature, 90+ CRI.
- ETL Safety listed for use in damp locations
- Compatible with many ELV dimmers
- Progress Lighting products are designed for exceptional quality, reliability, and functionality
- Includes installation instructions and mounting hardware
- Coordinating fixtures available
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" - ADA
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	34w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	
Lumens/LPW (Delivered)	2450/72 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30°C
Warranty	5-year limited warranty
Labels	cETLus Damp location listed ENERGY STAR® qualified Meets California Title 24 JA8-2016

Images:



Dimensions:

Width: 36"
 Depth: 3-1/2"
 Height: 4-3/4"
 H/CTR: 2-3/8" (horizontal)

Glass
 Width: 35-1/8"
 Height: 3"

P300209-009-30**Dimming Notes:**

is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTELV-300

Lutron DVELV-300P

Lutron DVCL-253P

Lutron Caseta

iDevices - IDEV0009

Lutron AYCL-153P

Lutron AYLV-600P

Lutron AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.