2" INGROUND - SUBMERSIBLE ROUND



2031

LANDSCAPE LIGHTING





Fixture Type:	
Catalog Number:	
Project:	
Location	

PRODUCT DESCRIPTION

Landscape 2" submersible recessed inground luminaire for up, down, side light applications. Comes with 30' long lead wire.

FEATURES

- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- 30' long lead wire and direct burial gel filled wire nuts included
- Includes a detachable stainless steel mounting bracket for use in or out of water
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

SPECIFICATIONS

Input: 9 - 15VAC (Transformer is required)

Power: 4.1W / 6.6VA Brightness: 170 lm Beam Angle: 25° CRI: 85

Rated Life: 70,000 hours

ORDERING NUMBER

	Color Temp		Finish	
2031 Submersible Round	30	3000K	ss	Stainless Steel

2031-30SS

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

2" INGROUND - SUBMERSIBLE ROUND



2031

LANDSCAPE LIGHTING

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max



TESTED MAGNETIC LOW VOLTAGE(MLV) DIMMERS

Luminaire	Dimmer							
	Manufacturer	Family	Model	Power Rating	Range*	Note		
2031		Diva	DVLV-600	600W	20% - 100%			
	Lutron	Skylark	SLV-600P	600W	15% - 100%	Best performance		
		Skylark	S-10P	1000W		Not recommended		

^{*}Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.