

Rose Gold Plated 3 pcs Basin Faucet Dual Ceramic Handle Mixer Tap



INSTALLATION INSTRUCTIONS

You may need/Usted puede necesitar/
Articles dont vous pouvez avoir besoin:



For easy installation

- To **READ ALL** the instructions completely before beginning.
- To **READ ALL** warnings, care, and maintenance information.
- To purchase the correct **water supply hook-up**.

1

A.

B.

C.

D.

A.

Slide hot (1) and cold (2) end valves with gasket (3) through sink. **Note:** Hot side endvalve is labeled (4). Secure end valves with washers (5) & threaded brackets (6). Hand tighten brackets (6) onto shank (7). Lock brackets into position by tightening screw (8). Install handles (9) on end valves and secure with set screw (12). **Be sure** glide ring (10) is properly seated in bottom of handles before installing. Push in button cover (11) to conceal set screw (12).

B.

Note proper end valve installation. Longer copper tubes (1) install away from spout.

C.

Install the spout (1) and gasket (2). Secure with washer and nut (3). **Note:** If sink is uneven, use silicone under the gasket.

D.

Align tabs (1) and tabs (2) on quick connects (3). Push quick connects firmly upward and snap onto receiving tube tab (1). Pull down moderately to ensure each connection has been made.

2

A.

B.

C.

D.

E.

F.

G.

H.

Metal Pop-up

A.

Remove stopper (1) and flange (2).

B.

Screw nut (1) all the way down. Push washer (2) and gasket (3) down.

C.

Remove tailpiece (1) from body (2), add plumber tape (3), replace tailpiece.

D.

Apply silicone to underside of flange (1). Insert body (2) into sink. Screw flange (1) into body (2).

E.

Pivot (1) must face faucet. Pull assembly (2) down firmly and hold in place. **DO NOT TWIST.**

F.

Tighten nut/washer / gasket (1), clean off excess silicone (2). **DO NOT TWIST.**

G.

Remove pivot nut (1). Install horizontal rod (2) and stopper (3) as removable (4) or non-removable (5). Hand tighten pivot nut (1).

H.

Attach horizontal rod (1) to strap (2) using clip (3). Insert lift rod (4) into strap and tighten screw (5). Connect assembly to drain (6).

3

4

This General diagram and installation instructions are not intended for any specific model, but is presented as a general guideline for Installations!