

Smooth baffle, square

When choosing a recessed fixture, eliminating glare is a priority. The unique positioning of the LED module in this series of downlights will meet that important need.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
RGR2SQ-3K	2"	8 W	600 lm	750 lm	90	3000 K	120 V
RGR4SQ-3K	4"	14 W	990 lm	1200 lm	90	3000 K	120 V
RGR6SQ-3K	6"	20 W	1600 lm	1900 lm	90	3000 K	120 V

Specifications

Every fixture includes a junction box with integrated dimmable driver
 Can be daisy chained
 Superior LED performance and lifespan
 Regressed light source
 Minimal heat emission
 Aluminum construction
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 40° beam angle
 Suitable for wet locations
 Refer to website for dimmer compatibility
 Ideal operating temperature:
 -20° to 40° C
 5-year warranty

Finish

- **BK** Black
- **SN** Satin Nickel
- **WH** White

Accessories

- RFP-UNI**
Universal rough-in plate
- RFP-23**
Rough-in plate for 2" and 3" models
- RFP-46**
Rough-in plate for 4" and 6" models

Order example

RGR2SQ-3K-SN
 Dimmable RGR2SQ-3K 2" square regressed LED fixture in a satin nickel finish

Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

