

P6342 Flood Light Head

 Fixture mounted • Wet location listed **PROGRESS LED**

Description:

The LED swivel flood light has tempered glass and rugged die-cast construction. For complete fixture order with P6343 backplate. 1,115 lumens 3000K color temperature, 83 CRI. 1/2" NPS treaded mounting. Adjustable swivel for easy adjustment. IP65 rated.

Specifications:

- Metallic Gray (-82) (Powder Coat Paint)
- Die-cast aluminum construction
- Tempered glass lens
- LED swivel flood light.
- Order back plate (P6343) separately.
- 1115 lumens, 84.5 lumens/watt
- 6" of wire supplied
-

Performance:

Number of Modules	1
Input Power	13w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1115/84.5 (LM-79)
CCT	3000 K
CRI	83
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed

P6342-8230K

Images:



Dimensions:

- (A) Diameter: 3-3/4"
- (C) Depth: 3-1/4"
- (B) Height: 5"

