# **KOHLER**<sub>®</sub>

# Features

- Two-piece toilet.
- Elongated bowl offers added room and comfort.
- Right-hand nested trip lever offers a choice of 1.1 or 1.6 gallons per flush (gpf).
- 2-1/8-inch glazed trapway.
- Coordinates with other products in the Wellworth collection.
- Combination consists of the K-4198 bowl and the K-4458-RA tank.
- Seat not included.

# Technology

 Dual-flush technology allows you to choose between a full- or partial-flush.

#### Installation

- Standard 12-inch rough-in.
- Three-bolt installation.

#### Water Conservation & Rebates

- WaterSense<sup>®</sup> toilets meet strict EPA flushing guidelines, including using at least 20 percent less water than 1.6-gallon toilets.
- Eligible for consumer rebates in some municipalities.

#### **Recommended Products/Accessories**

K-4636 Cachet® Quiet-Close™ Elongated Toilet Seat K-5588 Purefresh® Elongated Toilet Seat K-4108 C3®-230 Elongated Cleansing Toilet Seat K-5420 Low-Profile Bolt Caps K-9236 Trip Lever Dual Flush 1023457 Wax Ring/Hardware Kit 1265114 Connector Hose

#### **Included Components**

Product consists of: K-4458-RA Dual-Flush Tank K-4198 Elongated Bowl K-9236 Trip Lever Dual Flush Additional Components: Bolt cap accessory pack Bowl Tank Tank Tank cover Trip lever





# Codes/Standards

ASME A112.19.2/CSA B45.1 EPA WaterSense®

# KOHLER<sup>®</sup> One-Year Limited Warranty

See website for detailed warranty information.

# **Available Colors/Finishes**

Color tiles intended for reference only.

#### Color Code Description

0	White
96	Biscuit
47	Almond



# **Wellworth®** Class Five<sup>®</sup> Dual Flush Toilet

K-3988-RA



# Wellworth® Class Five® Dual Flush Toilet K-3988-RA



# **Technical Information**

All product dimensions are nominal.			
Toilet type:	Two-piece, Floor-mount		
Waste Outlet:	Floor		
Bowl shape:	Elongated		
Flush type:	Class Five®		
Trap passageway:	2-1/8" (54 mm)		
Water Consumption			
Full:	1.6 gpf (6 lpf)		
Reduced:	1.1 gpf (4.3 lpf)		
Water surface size:	11-1/4" x 8-1/4" (286 mm x 210 mm)		
Rim to water surface:	5-1/4" (133 mm)		
Rough-in:	12" (305 mm)		
Seat-mounting holes:	5-1/2" (140 mm)		

#### Notes

Install this product according to the installation instructions.

