

## LED Wall Bracket

 Wall mounted • Damp location listed 

### Description:

Parallel LED vanity and sconces feature a tubular opal glass diffuser paired with a simple, modern metal canopy. An integrated LED source provides a variety of energy and cost savings benefits. Suitable for residential and commercial applications.

### Specifications:

- Architectural Bronze (-129) (painted)
- Steel construction
- Etched White Glass Cylindrical
- A cylindrical design pairs with an oval back plate to create a harmonious design
- 11" linear 16-watt LED wall bracket
- Integrated LED source provides a variety of energy and cost savings benefits for the homeowner
- Measures 4 3/4" W x 7 1/2" H
- 918 lumens 56 lumens/watt (delivered)
- Warm white 3000K lighting color and 90+CRI
- Modern style and continuous illumination are ideal for a variety of bath and vanity settings - including Mid-Century and Luxe
- Damp location listed
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting plate for outlet box included
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" - ADA
- Meets California Title 24 JA8-2016

### Performance:

|                        |   |
|------------------------|---|
| Number of Modules      | 1   |
| Input Power            | 16w   |
| Input Voltage          | 120 V   |
| Input Frequency        | 60 Hz   |
| Lumens/LPW (Delivered) | 918/56.7 (LM-79)  |
| CCT                    | 3000 K  |
| CRI                    | 90 CRI  |
| Life (hours)           | 50,000 (L70/TM-21)  |
| FCC                    | Meets FCC Title 47, Part 15 Class B                               |
| Min. Start Temp        | -10 °C  |
| Warranty               | 5 year limited warranty   |
| Labels                 | cETLus Damp location listed<br>Meets California Title 24 JA8-2016 |

## P710050-129-30

### Images:



### Dimensions:

Width: 4-3/4"  
Depth: 2-3/4"  
Height: 11"  
H/CTR: 7-1/2"

Glass  
Width: 1-15/16"  
Length: 1-15/16"  
Height: 9-15/16"

**P710050-129-30****Dimming Notes:**

---

P710050 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron - NTELV-300

Lutron - DVELV-300P

Lutron - DVCL-253P

Lutron - Caseta Wireless

Leviton – 6672

Leviton – 6674

Leviton - 6681

Lutron - AYCL-153P

Lutron - TGCL-153PH

Lutron - AYLV-600P

Lutron - NTLV-600

Lutron - MAELV-601

Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.